

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Sanders Oil & Gas</u>		Lease <u>Cannon "A" et al</u>		Well # <u>1</u>	
Location of Well	Unit <u>I</u>	Section <u>18</u>	Township <u>10</u>	Range <u>25</u>	County <u>CHAVES</u>
Drilling Contractor	<u>YOUNG</u>		Type of Equipment <u>ROTARY</u>		
* WITNESS <u>APPROVED CASING PROGRAM</u>					
Size of Hole	Size of Casing <u>12 3/4"</u>	Weight Per Foot	New or Used	Depth <u>185'</u>	Sacks Cement <u>circ.</u>
<u>12 1/4</u>	<u>8 5/8</u>	<u>24</u>	<u>NEW</u>	<u>900</u>	<u>circ</u>
<u>7 7/8</u>	<u>4 1/2</u>	<u>9.5</u>	<u>"</u>	<u>4250</u>	<u>450</u>
Casing Data:					
Surface _____ joints of _____ inch _____ # Grade _____					
(Approved) (Rejected) _____					
Inspected by _____ date _____					
Cementing Program					
Size of hole <u>11"</u> Size of Casing <u>8 5/8"</u> Sacks cement required _____					
Type of Shoe used <u>guide</u> Float collar used <u>insert</u> Btm 3 jts welded <u>yes</u>					
TD of hole <u>700'</u> Set <u>700'</u> Feet of <u>8 5/8"</u> Inch <u>24</u> # Grade <u>J-55</u>					
New-used csg. @ <u>700'</u> with <u>100</u> sacks neat cement around shoe					
+ <u>225</u> sax <u>B. J. L. E.</u> additives <u>- 0 -</u>					
Plug down @ <u>3:30</u> (AM) (PM) Date <u>5/29/83</u>					
Cement circulated <u>No</u> No. of Sacks <u>- 0 -</u>					
Cemented by <u>B. J. Hughs</u> Witnessed by <u>Mike Stillfield</u>					
Temp. Survey ran @ <u>10:00</u> (AM) (PM) Date <u>5/23/83</u> top cement @ <u>195'</u>					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: _____					

Full return to TD.					

1. Ran 1" r Tagged to c @ 190'
w/ 50 s x C 390 -
2. Ran 1" r Tagged to c @ 90'
w/ 125 s x C
cement circulated to surface.