


C - CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	☒
FILE	☒
U.S.G.S.	
LAND OFFICE	☒
OPERATOR	☒

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR TO REWORK AN EXISTING WELL IN A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.



5a. Indicate Type of Lease State ☐ Fee ☐	
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name Cannon "A" Com.	
9. Well No. 1	
10. Field and Pool, or Wildcat Undesignated Abo	
12. County Chaves	

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator
Sanders Oil & Gas Company

3. Address of Operator
14679 Midway Road, #101, Dallas, Texas 75234

4. Location of Well
UNIT LETTER 1 1980 FEET FROM THE South LINE AND 660 FEET FROM
East THE LINE, SECTION 18 TOWNSHIP 10S RANGE 25E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3525 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPS. ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☒	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

May 11, 1983 - Move in cable tool rig

12 - R.U.

13 - R.U. Drill 10' cement in conductor

14 - Drill to 160'

15 - Clean out caving

16 - Down

17 - Down

18 - Drive 12 3/4" casing to 145' - 42# casing

19 - Drive 12 3/4" casing to 165'

20 - Drive 12 3/4" casing to 185'

23 - Mud hole & move off hole

26 - Move in rotary & R.U. - cement 12 3/4" w/50 sxs. class cement. Circulate to pits. WOC 18 hrs. - Test to 1000 p.s.i. - 1 hr. - OK

27 - Drill to 11 5/8" hole to 700'. Run 700' of 8 5/8", 24# casing. Cemented w/100 sxs. Class "C" and 225 sxs. of B.J. Lite - Cement did not circulate.

28 - Ran temp. survey - Top of cement at 185'. Ran 1" and spotted 50 sxs. plug. Tagged top cement at 84' - Spotted 125 sxs. cement. Circulated to pits. Nipped up and tested B.O.P. and casing - OK Tested to 1000 p.s.i. for 1 hr.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Exploration Manager DATE 9-26-83

APPROVED BY [Signature] TITLE Supervisor District # DATE SEP 29 1983