	MOTI CONS.	COMMISSION	alsF .
Form 9–331 Dec. 1973	Drawer DD Artesia, NK	88210 Form Approv Budget Bure	red. au No. 42R1424
UNITED STATE		5. LEASE	· · · · · · · · · · · · · · · · · · ·
DEPARTMENT OF THE	INTERIOR	NM 11103	
GEOLOGICAL SUR	VEY	6. IF INDIAN, ALLOTTEE OR TH	RIBE NAME
SUNDRY NOTICES AND REP (Do not use this form for proposals to drill or to de		7. UNIT AGREEMENT NAME	<u></u>
reservoir. Use Form 9+331+C for such proposals.)	epen of plag back to a different	8. FARM OR LEASE NAME	AUC 0.0 1000
1. oil gas 🗊		Globe MN Federal	AUG 09 1983
well well X other		9. WELL NO.	
2. NAME OF OPERATOR			0. C. D.
Yates Petroleum Corporatio	on	10. FIELD OR WILDCAT NAME	ARTESIA, OFFICE
3. ADDRESS OF OPERATOR		Pecos Slope Abo	
207 South 4th St., Artesia	a. NM 88210	11. SEC., T., R., M., OR BLK. AI	ND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATIC below.)		AREA Unit K, Sec. 1-T5S-	
AT SURFACE: 1980 FSL & 1880 I	FWL, Sec. 1-5S-24E	12. COUNTY OR PARISH 13.	STATE Internet
AT TOP PROD. INTERVAL: 1982		Chaves NI	4
AT TOTAL DEPTH:		14. API NO.	: ب ب • • •
16. CHECK APPROPRIATE BOX TO INDICA	ATE NATURE OF NOTICE,		k - 1-
REPORT, OR OTHER DATA		15. ELEVATIONS (SHOW DF, H	(DB, AND WD)
		3872.1' GR	
	SEQUENT REPORT OF:		C
TEST WATER SHUT-OFF FRACTURE TREAT	X	70	JUL
SHOOT OR ACIDIZE		<u></u>	R 22
REPAIR WELL		(NOTE: Report results of multiple	TO TO NOT
PULL OR ALTER CASING		(NOTE: Report results of multiple change on Form 9-330.)	n
MULTIPLE COMPLETE		• • • • • • • • • • • • • • • • • • •	
CHANGE ZONES		ے۔ ج	
ABANDON*			
		<u> </u>	
17. DESCRIBE PROPOSED OR COMPLETED	OPERATIONS (Clearly state	all pertinent details, and give r	ertinent dates.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 14-3/4" hole 6:15 PM 7-16-83. Set 40' of 20" conductor pipe. Ran 26 joints of 10-3/4" 40.5# J-55 casing set 800'. 1-Texas Pattern notched guide shoe set 800'. Insert float set 767'. Cemented w/400 sacks Pacesetter Lite, 3% CaCl2. Tailed in w/300 sacks Class "C" 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hours. PD 8:30 PM 7-17-83. Bumped plug to 1000 psi, released pressure and float held okay. WOC. Drilled out at 2:30 PM 7-18-83. WOC 18 hours. Nippled up and tested to 1000#, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

SIGNED . unilant to d	Production	
ć	(This space for Federal or State office use)	ACCEPTED FOR RECORD
APPROVED BY CONDITIONS OF APPROVAL, IF ANY:	TITLE	AUG 8 1983
	*See Instructions on Reverse Side	ROSWELL, NEW MEXICO