

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐  
well well

2. NAME OF OPERATOR  
Cibola Energy Corporation

3. ADDRESS OF OPERATOR  
P.O. Box 1668, Albuquerque, New Mexico 87103

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 990 FSL & 330 FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☒

(other) Plug back

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

RECEIVED BY

OCT 04 1983

O. C. D.

ARTESIA, OFFICE

NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

TD 2310'

We propose to circulate hole with f/w gell and plug as follows:

- 1st plug, 40 sx cmt, 2310-2180, top Slaughter 2217
- 2nd plug, 35 sx cmt, 1640-1540, top San Andres 1588
- 3rd plug, 35 sx cmt, 1210-1110, top Queen 1059
- 4th plug, 35 sx cmt, 475-375, surface casing at 425
- 5th plug, 10 sx cmt at surface with dry hole marker

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Karen Azar TITLE Drilling Secretary DATE 9/22/83

APPROVED

(This space for Federal or State office use)

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

OCT 3 1983

DATE