

NM OIL CONS. COMMISSION  
Drawer DD  
Artesia, NM 88210

Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

RECEIVED

SEP 26 2 51 PM '83

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐  
well well
2. NAME OF OPERATOR  
ENSERCH EXPLORATION, INC.
3. ADDRESS OF OPERATOR 75247  
1230 River Bend Drive - Suite 136, Dallas, TX
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 560' FNL & 890' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

- |                      |                          |                          |
|----------------------|--------------------------|--------------------------|
| TEST WATER SHUT-OFF  | <input type="checkbox"/> | <input type="checkbox"/> |
| FRACTURE TREAT       | <input type="checkbox"/> | <input type="checkbox"/> |
| SHOOT OR ACIDIZE     | <input type="checkbox"/> | <input type="checkbox"/> |
| REPAIR WELL          | <input type="checkbox"/> | <input type="checkbox"/> |
| PULL OR ALTER CASING | <input type="checkbox"/> | <input type="checkbox"/> |
| MULTIPLE COMPLETE    | <input type="checkbox"/> | <input type="checkbox"/> |
| CHANGE ZONES         | <input type="checkbox"/> | <input type="checkbox"/> |
| ABANDON*             | <input type="checkbox"/> | <input type="checkbox"/> |
- (other) Report of Drilling Operations

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 8-3/4 inch hole to total depth of 8363'. A suite of logs was run and the decision made to run 4-1/2 inch, 11.6#, K-55, STC casing to total depth. Cemented with 1650 sacks Class H + 0.8% CF-1 + 3% KCL + 0.2% AF-5 + 1#/sack Hi-seal. Plug down at 9:20 A.M. 9-9-83. Float did not hold; held under pressure for eight hours. Released rig 9-9-83.

Subsequent reports for this well will be submitted by our Production Office in Midland, Texas

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED C. H. Peeples TITLE Rgl. Drilling Mgr DATE September 22, 1983

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

SEP 27 1983

\*See Instructions on Reverse Side

ROSWELL, NEW MEXICO