

C/SF

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other ☒ Dry

2. NAME OF OPERATOR

Enserch Exploration, Inc. ✓

3. ADDRESS OF OPERATOR

P. O. Box 4315, Midland, Texas 79704

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 560' FNL & 890' FWL

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

5. LEASE NM-18989	
6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
7. UNIT AGREEMENT NAME	
8. FARM OR LEASE NAME Harper Federal	
9. WELL NO. 1	RECEIVED BY JAN 24 1985 O. C. D. ARTESIA, OFFICE
10. FIELD OR WILDCAT NAME Wildcat - <i>Furness</i>	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 13, T6S, R29E	
12. COUNTY OR PARISH Chaves	13. STATE New Mexico
14. API NO. 30-005-62033	
15. ELEVATIONS (SHOW DF, KDB, AND WD) 4200.9' GR	

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Set CIBP at 7050'. Tested to 500#.  
Circulated 10# mud laden fluid.  
Cut off 4-1/2" casing at 4000'.  
Laid 60 sack Class C cement plug from 4050'-3950'. Tagged.  
Laid 75 sack Class C cement plug from 2135'-2035'. Tagged.  
Laid 20 sack Class C cement plug from 50' to surface.  
Cut off 9-5/8" casinghead and welded 9-5/8" x 1/2" steel plate.  
Installed dry hole marker December 31, 1983.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *H. F. B...* TITLE Prod. Superintendent DATE 1/16/84

APPROVED

(This space for Federal or State office use)

APPROVED (Only Sgd.) PETER W. CHESTER

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: