

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER DP  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Pet. Co</u>			Lease <u>Grooms XB com</u>		Well # <u>1</u>
Location of Well	Unit <u>M</u>	Section <u>8</u>	Township <u>7</u>	Range <u>26</u>	County <u>CHAVES</u>
Drilling Contractor	<u>UND.</u>		Type of Equipment <u>ROTARY</u>		
<p><b>* Witness</b> <span style="float: right;"><u>APPROVED CASING PROGRAM</u></span></p>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>* 14 3/4"</u>	<u>10 3/4"</u>	<u>40.5</u>	<u>NEW</u>	<u>850</u>	<u>CIRC</u>
<u>7 7/8</u>	<u>4 1/2"</u>	<u>9.5</u>	<u>"</u>	<u>TD</u>	<u>350</u>
Casing Data:					
Surface <u>20</u> joints of <u>10 3/4</u> inch <u>40.5</u> # Grade <u>J-55</u>					
(Approved) (Rejected) <u>Yes</u>					
Inspected by <u>B.W. Weaver</u> date <u>8-14-83</u>					
Cementing Program					
Size of hole <u>14 3/4</u> Size of Casing <u>10 3/4</u> Sacks cement required <u>          </u>					
Type of Shoe used <u>14 3/4</u> Float collar used <u>Insert</u> Btm 3 jts welded <u>yes</u>					
TD of hole <u>800</u> Set <u>807</u> Feet of <u>10 3/4</u> Inch <u>40.5</u> # Grade <u>J-55</u>					
New-used csg. @ <u>807</u> with <u>30</u> sacks neat cement around shoe					
+ <u>000</u> sack <u>Pace Setter 1 lb</u> additives <u>3% cc</u>					
Plug down @ <u>1:15</u> ( <u>PM</u> ) Date <u>8-14-83</u>					
Cement circulated <u>yes</u> No. of Sacks <u>          </u>					
Cemented by <u>Wester</u> Witnessed by <u>B.W. Weaver</u>					
Temp. Survey ran @ <u>          </u> (AM) (PM) Date <u>          </u> top cement @ <u>          </u>					
Casing test @ <u>          </u> (AM) (PM) Date <u>          </u>					
Method Used <u>          </u> Witnessed by <u>B.W. Weaver</u>					
Checked for shut off @ <u>          </u> (AM) (PM) Date <u>          </u>					
Method used <u>          </u> Witnessed by <u>          </u>					
Remarks: <u>Last Drill as Spec 680 2-</u>					