5. LEASE

žx ν

Artesia, NN 88210

Form Approved. Budget Bureau No. 42-R1424

UNITED STATES DEPARTMENT OF THE INTERIOR

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	NM 27794 6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
GEOLOGICAL SORVET	N/A	
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAI , N/A	RECEIVED BY
reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME Sorenson Federa	AUG 29 1983
1. oil gas well other	9. WELL NO. 2	O. C. D.
2. NAME OF OPERATOR		- ARTESIA, OFFICE
Stevens Operating Corporation 3. ADDRESS OF OPERATOR	Wildest San Andres	
P. O. Box 2408, Roswell, NM 88201	11. SEC., T., R., M., OR BLK. AND SURVEY OR	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA	
below.)	Sec. 18 T-7-S R-	
AT SURFACE: 1980 FSL 330 FEL Sec 18 T7S R27E	12. COUNTY OR PARISH	
AT TOP PROD. INTERVAL: Same AT TOTAL DEPTH: Same	Chaves	NM
Danc	14. API NO.	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE		05 (00 100 00)
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW	DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	3954.6 GR	
TEST WATER SHUT-OFF		
FRACTURE TREAT	***** p**	, <u>, , , , , , , , , , , , , , , , , , </u>
SHOOT OR ACIDIZE	õõ	
REPAIR WELL	(NOTE: Report results of first change on Form 9-3	
PULL OR ALTER CASING	Pro-	R E
CHANGE ZONES	Proce Proce	·
ABANDON*	10 m 1 21 m	EIVE
(other) Spud, casing, TD X	رورد (المحمد المحم المحمد المحمد المحم المحمد المحمد المحم) <u>F</u>
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertin	s directionally drilled, give subs	give pertinent dates, surface locations and
8- 9-83 Spud @ 2:00 P.M. w/12½" hole.		
8-10-83 Ran 7 jts. 8 5/8" x 24.0# K-55 csg. "C" cement w/2% CC & 1/4# per sx flo-sa sxs, plug held. WOC 18 hrs. Pressur pressure decrease.	11. Plug down @ 2:00	P.M., circ 100
8-13-83 Reached TD 1818' @ 4:00 P.M. Spot 2 trip out to log.	bbls. 2% KCL water o	n bottom and
8-14-83 Ran 45 jts. 4 1/2" x 11.6# K-55 8 RD sxs. 50/50 POZ w/2% CC. Plug down @ 5:00 P.M. WOC 18 hrs. Pressure up pressure decrease.	4:30 P.M., plug held	. Rig released
	.	C

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct Production

TITLE Controller

TITLE

DATE August 22, 1983

APPROVED BY CONDITIONS OF APPROVAL, IF ANY: DATE