

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Brady Prod. Co.</u>			Lease <u>Sturgeon A</u>		Well # <u>2</u>
Location of Well	Unit <u>H</u>	Section <u>5</u>	Township <u>7</u>	Range <u>26</u>	County <u>Chaves</u>
Drilling Contractor	<u>Brady Dring. Co.</u>		Type of Equipment <u>Rotary</u>		
<p>* Witness <u>APPROVED CASING PROGRAM</u></p>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>9 5/8</u>	<u>7"</u>	<u>23#</u>	<u>NEW</u>	<u>100</u>	<u>circ.</u>
* <u>6 1/4</u>	<u>4 1/2"</u>	<u>11.6#</u>	<u>"</u>	<u>1050</u>	<u>circ.</u>
Casing Data:					
Surface <u>26</u> joints of <u>4 1/2</u> inch <u>11.6</u> # Grade <u>J-55</u>					
<u>yes</u> (Approved) (Rejected)					
Inspected by <u>B.W. Weaver</u> date _____					
Cementing Program					
Size of hole <u>6 1/4</u> Size of Casing <u>4 1/2</u> Sacks cement required <u>50</u>					
Type of Shoe used <u>Tex-Ar</u> Float collar used <u>Insert</u> Btm 3 jts welded <u>Yes</u>					
TD of hole <u>1067</u> Set <u>1070</u> Feet of <u>4 1/2</u> Inch <u>11.6</u> # Grade <u>J-55</u>					
New-used csg. @ <u>1070</u> with <u>50</u> sacks neat cement around shoe					
+ <u>100</u> sax <u>Danell lite</u> additives <u>29.00</u>					
Plug down @ <u>5:50</u> (AM) (PM) Date <u>11-24-13</u>					
Cement circulated <u>yes</u> No. of Sacks <u>40</u>					
Cemented by <u>Danell</u> Witnessed by <u>B.W. Weaver</u>					
Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: <u>Water Zone @ 58 to 70 ft</u>					