

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	<input checked="" type="checkbox"/>
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87504
SEP 28 1983
O. C. D.
ARTESIA, OFFICE

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
LG-8968

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO OPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 S. 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER C 660 FEET FROM THE North LINE AND 1980 FEET FROM
THE West LINE, SECTION 22 TOWNSHIP 9S RANGE 26E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name

Nortex "WN" State

9. Well No.

1

10. Field and Pool, or Wildcat

~~Under~~ Pecos Slope Abo

11. Elevation (Show whether DF, RT, GR, etc.)

3773.1' GL

12. County

Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOB ☒

OTHER ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 14-3/4" hole 10:30 am 9-20-83. Set 40' of 20" conductor pipe. Ran 25 joints 8-5/8" 24# J-55 ST&C casing set 1000'. 1-Texas Pattern notched guide shoe set 1000'. Insert float set 959'. Cemented with 300 sacks Pacesetter Lite 3% CaCl₂. Tailed in with 300 sack Class "C" 20 CaCl₂. Compressive strength of cement - 1250 psi in 12 hours. PD 8:30 am 9-22-83. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 35 sacks. WOC. Drilled out 2:30 am 9-23-83. WOC 18 hours. Nipped up and tested to 1000# for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Leslie A. Clements

TITLE Production Supervisor

DATE 9-27-83

APPROVED BY

Original Signed By
Leslie A. Clements

TITLE

DATE

SEP 29 1983

CONDITIONS OF APPROVAL, IF ANY: Supervisor District II