

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

RECEIVED

JAN 3 10 30 AM '84

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
Mesa Petroleum Co.

3. ADDRESS OF OPERATOR
P. O. Box 2009/Amarillo, TX 79189

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL & 1980' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) Spud, 10 3/4" csg & cement		

5. LEASE
NM-29207

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME RECEIVED BY

8. FARM OR LEASE NAME
Francis Fed Com JAN 10 1984

9. WELL NO.
1 O. C. D.
ARTESIA, OFFICE

10. FIELD OR WILDCAT NAME
Undes. Pecos Slope Abo

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 13, T8S, R25E

12. COUNTY OR PARISH
Chaves

13. STATE
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3546' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 14 3/4" hole on 12/22/83.

TD 14 3/4" hole on 12/24/83. Ran 23 jts 10 3/4", 40.5#, J-55, ST&C csg @ 915'.

Cmtd w/500 sx "C" + 10% gypseal + 4% CaCl₂. Tailed in w/200 sx "C" +2% CaCl₂.

PD @ 2200 hr. Circ. 100 sx. Tested csg and BOP to 600 psi for 30 min. - ok.

Reduced hole to 7 7/8" and drilled ahead on 12/27/83. WOC total of 18 hrs.

ACCEPTED FOR RECORD

JAN 6 1984

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED R. E. Mackin TITLE Regulatory Coordinator DATE 12/28/83

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

xc: BLM-R (0 + 6), Cen Rdcs, Actg, Mat Cont, Ops (File), Roswell, Midland, Partners