

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

RECEIVED BY
DEC 28 1983
O. C. D.
ARTESIA OFFICE

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well gas well other

2. NAME OF OPERATOR
McClellan Oil Corporation

3. ADDRESS OF OPERATOR
P.O. Drawer 730, Roswell, NM 88201

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL & 660' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other) Casing & Cement			

5. WELL NO. NM-0559993

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
MM Comm Federal *Comm.*

9. WELL NO.
2

10. FIELD OR WILDCAT NAME
South Pecos Slope *abo*

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 35-T9S-R25E

12. COUNTY OR PARISH | 13. STATE
Chaves | NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3614' G.L.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12/9/83: TD at 4400', logged with Schlumberger CNL-FDC. Ran 4400' of 4-1/2" 10.5 lb/ft casing. Cemented with 350 sx Class "C", 50/50 Pozmix. Nipple up wellhead. Release rig.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *David R. Glass* TITLE Operations Manager DATE 12/14/83

ACCEPTED FOR RECORD (This space for Federal or State office use)

APPROVED BY (ORIG. SGD.) DAVID R. GLASS TITLE _____ DATE _____

CONDITIONS OF APPROVAL _____
DEC 27 1983