

NM OIL CONS. COMMISSION

Drawer D

Artesia, NM 88210

Form 9-331  
(May 1963)

DEPARTMENT OF THE INTERIOR (Other instructions on re-  
verse side)

SUBMIT IN TRIPLICATE

Form approved.

BUDGET BUREAU No. 42-R142

5. LEASE DESIGNATION AND SERIAL N  
NM-14472

6. IF INDIAN, ALLOTTEE OR TRIBE N

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or re-drill or plug back to  
a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals.)

1. OIL GAS  
WELL ☒ WELL ☐ OTHER

2. NAME OF OPERATOR  
Read & Stevens, Inc.

3. ADDRESS OF OPERATOR  
P.O. Box 1518, Roswell, NM 88201

4. LOCATION OF WELL (Report location clearly and in accordance with State  
requirements.\* See also space 17 below.)  
At surface

1980' FNL and 560' FWL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Palma Mesa Federal

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT  
Wildcat

11. SEC. T., R., M., OR BLK. AND  
SURVEY OR AREA  
Sec. 6-9S-28E

14. PERMIT NO.

15. ELEVATIONS (Show whether OF, RT, GR, etc.)  
3905' MSL

12. COUNTY OR PARISH  
Chaves

13. STATE  
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF  
FRACTURE TREAT  
SHOOT OR ACIDIZE  
REPAIR WELL  
(Other)

PULL OR ALTER CASING  
MULTIPLE COMPLETE  
ABANDON\*  
CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF  
FRACTURE TREATMENT  
SHOOTING OR ACIDIZING  
(Other) Spud, ran csg, sidewall core

REPAIRING WELL  
ALTERING CASING  
ABANDONMENT\*

(NOTE: Report results of multiple completion on We  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including  
estimated date of starting any proposed work. If well is directionally drilled give subsurface locations and measur  
and true vertical depths for all markers and zones pertinent to this work.)\*

11-23-83 Spud 11" hole @ 7:00am 11-23-83.

11-24-83 Spud 12 1/4" hole @ 7:00am 11-23-83. TD 12 1/4" @ 3:30am 11-24-83 @ 465'.

11-25-83 Ran 11 jts, 457', 8 5/8"-24#, J-55 ST&C, used csg insert float @ 422' set @ 465'.  
Cement w/ 350sx Class "C" cmt 2% CC, circ 50sx. PD @ 7:45 11-24-83. Bump plug @  
300psi. Test BOP & csg @ 1000psi for 30min. Tested satisfactorily.

11-26-83 18hrs WOC.

I hereby certify that the foregoing is true and correct

SIGNED

TITLE Drilling & Production Manager

DATE 11-28-83

(This space for use by State or Office use)

APPROVED BY

(ORIG. SCD.) DAVID R. GLASS

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side