

215F

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well ☐ gas well ☐ other ☐ PSA
2. NAME OF OPERATOR
Yates Petroleum Corporation ✓
3. ADDRESS OF OPERATOR
207 South 4th St., Artesia, NM 88210
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1450 FNL & 660 FWL, Sec. 26-10S-25E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input checked="" type="checkbox"/>
(other)		

5. LEASE
NM 07384
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Rolling Hills YQ Federal
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Pecos Slope Abo
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Unit E, Sec. 26-T10S-R25E
12. COUNTY OR PARISH
Chaves
13. STATE
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3788.1' GR

RECEIVED BY
AUG 15 1985
O. C. D.
ARTESIA, OFFICE

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plugged well as follows: Set 35 sacks Class "C" 2% CaCl plug at 4135'. WOC 3 hrs. PD 9:00 PM 2-27-84. Tagged cement 3970'. Set 35 sacks Class "C" 2% CaCl2 plug at 1935'. PD 1:00 AM 2-28-84. WOC 3 hrs. Tagged cement 1830'. Set 50 sacks Class "C" 2% CaCl2 plug at 890'. PD 6:30 AM 2-28-84. WOC 2-1/2 hrs. Tagged cement 800'. Set 30 sacks Class "C" Neat plug at surface. PD 9:30 AM 2-28-84. Installed dry hole marker, cleaned location.

Verbal permission given by Peter Chester, BLM, Roswell for above plugging procedure.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct.

SIGNED Peter Chester TITLE Production Supervisor DATE 2-29-84

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

APPROVED
PETER W. CHESTER
AUG 13 1985
BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA