

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Yates Pet Corp</u>		Lease <u>Caudill R2 com</u>		Well # <u>6</u>	
Location of Well	Unit <u>A</u>	Section <u>18</u>	Township <u>6</u>	Range <u>26</u>	County <u>Chaves</u>
Drilling Contractor	<u>L & M</u>		Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>14 3/4</u>	<u>10 3/4</u>	<u>40.5</u>	<u>New</u>	<u>955</u>	

Casing Data:

Surface 26 joints of 10 3/4 inch 40.5 # Grade J-55
yes (Approved) (Rejected)

Inspected by BW Weaver date 4-16-84

Cementing Program

Size of hole 14 3/4 Size of Casing 10 3/4 Sacks cement required 200

Type of Shoe used Ter-Pat Float collar used Insert Btm 3 jts welded yes

TD of hole 950 Set 960 Feet of 10 3/4 Inch 40.5 # Grade J-55

New-~~wood~~ csg. @ 960 with 200 sacks neat cement around shoe
 + 400 sax Hewco lite 3 1/2 cc additives

Plug down @ 10:30 (AM) (PM) Date 4-16-84

Cement circulated yes No. of Sacks 30

Cemented by Hewco Witnessed by B.W. Weaver

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Last Drilling Break 823