O+6-BLM-Roswell, 1-File, 1-Engr PWS, 1-Foreman HS, 1 Form 9-331 1-JA, 1-BB	l-Mr. J.AMidland, l-Laura Richardso Form Approved.
Drawer DD COMUISSI	Budget Bureau No. 42-R1424
UNITED STATES TO DD DEPARTMENT OF THE INTERIOR _88210	NM-54991
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas 🔯 other	Getty P.S. 18 Federal 9. WELL NO.
2. NAME OF OPERATOR	10. FIELD OR WILDCAT NAME
Getty Oil Company 3. ADDRESS OF OPERATOR	Pecos Slope Abo
P.O. Box 730, Hobbs, NM 88240	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA Sec. 18, T-6S, R-26E
AT SURFACE: Unit Ltr. N, 660' FSL & 1980' FWL AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE NM
AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.
REPORT, OR OTHER DATA REPORT FOR APPROVAL TO: SUBSEQUENT REPORT OF:	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3746.2 GR
TEST WATER SHUT-OFF	irectionally drilled, give substitute that work.)* K-55, 40.5#, 8rd, ST&C, R-3, A 839'. Cemented w/ 450 sxs lite w/ aCl2. Plugged down @ 5:00 P.M. 10.5#, 8rd, (4189') casing set @ 155'. 1st stage Howco w/ 950 sxs ost circ. while cementing, open DV and stage w/ 600 sxs lite w/ 5# salt, 3% Halad-4. Plugged down @ 4:45 P.M.
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
	endentare March 26, 1984
(This space for Federal or State of	fice use)
APPROVED BY CONDITIONS O APPROVED THE TITLE	DATE
/.PR 9 1984	
*See Instructions on Reverse	No. 19 No. 2 No.