


OIL CONSERVATION
P. O. BOX 2088
SANTA FE, NEW MEXICO

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	☒
FILE	☒
U.S.G.S.	☒
LAND OFFICE	☒
OPERATOR	☒



3a. Indicate Type of Lease	
State ☒	Fee ☐
3. State Oil & Gas Lease No.	
LH-1144	

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

OIL WELL ☐	GAS WELL ☒	OTHER ☐	7. Unit Agreement Name
Name of Operator			8. Farm or Lease Name
T. H. McElvain Oil & Gas Properties ✓			Corn Gulf State
Address of Operator			9. Well No.
P.O. Box 2148, Santa Fe, NM 87504-2148			1
Location of well			10. Field and Pool, or Wildcat
UNIT LETTER <u>P</u> <u>825</u> FEET FROM THE <u>South</u> LINE AND <u>825</u> FEET FROM			Wildcat Abo
THE <u>East</u> LINE, SECTION <u>25</u> TOWNSHIP <u>8S</u> RANGE <u>21E</u> N.M.P.M.			
15. Elevation (Show whether DF, RT, GR, etc.)			12. County
4125' KB			Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPER. ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Set 40' of 13 3/8" conductor, ready-mix to surface. Spudded well at 22:00 on 3-9-84. Drilled 12 1/4" hole to 1029'. Spotted open hole cement plugs as follows in an effort to get 8 5/8" casing to bottom: Plug #1 @ 518' - 100 sks Class C + 2% CaCl + 5 lb./sk HySeal
Plug #2 @ 500' - 100 sks Class C + 2% CaCl + 5 lb./sk HySeal
Plug #3 @ 500' - 200 sks Class C + 4% CaCl
Plug #4 @ 490' - 200 sks Class C + 4% CaCl
Plug #5 @ 535' - 200 sks Class C + 4% CaCl
Plug #6 @ 562' - 200 sks Class C + 4% CaCl

Cleaned out hole to 981'. Ran Western Texas Patter Guide Shoe and 23 jts. 8 5/8", 23#, X-42, ST&C casing, set at 958' KB. Insert float in collar of shoe and collar of shoe jt. (44.15' above shoe). Welded shoe to shoe jt. and shoe jt. to second jt. Pumped 20 bbls fresh water gel ahead of cement. Mix and pump 300 sks Western Lite with 1/4# flocele/sk + 5# HySeal/sk (slurry wt. - 12.4 ppg) followed by 200 sks Class C with 2% CaCl (slurry wt. - 14.8 ppg). Displaced with 56 bbls fresh water. Bumped plug with 400 psi net. Plug down at 12:15 on 3-16-84. Ran temperature survey at 18:00 (copy enclosed) and found cement top at 450'. Ran 1" to 490' and spotted plug #1 - 150 sks Class C + 4% CaCl. Ran 1" to 480' and spotted plug #2 - 150 sks Class C + 4% CaCl. Ran 1" to 124' and spotted plug #3 - 75 sks Class C + 4% CaCl. Circulated 20 sks to surface. Cement fell back. Ready mix to surface with 2 yds Neat cement and filled cellar with 6" at base, no fall back. WOC 22 hrs. Test casing to 1000 psi for 1/2 hr. with blind rams and 1/2 hr. with pipe rams, held ok. Drilled out of shoe at 16:30 on 3-17-84.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Leslie A. Clements TITLE Geological Engineer DATE March 21, 1984
Original Signed By
Leslie A. Clements
Supervisor District II
DATE MAR 26 1984



BENNETT-CATHEY WIRE LINE SERVICE

P. O. BOX 787 / ARTESIA, NEW MEXICO 88210 / PHONE 746-3281

C. C. D.

WIRE LINE

TEMPERATURE SURVEY



OPERATOR T.H. MC ELVAIN

LEASE CORN GULF STATE

WELL NO. #1

COMPANY REPRESENTATIVE JOHN SHELDON

DATE & TIME CEMENT JOB COMPLETED 1200 HOUR 3-16-84

DATE & TIME SURVEY MADE 1800 HOUR 3-16-84

SURVEY RUN BY BO FAULKENBERRY

WELL DATA CEMENT TOP 450 FEET

TOTAL DEPTH 855 FEET

MEASURED FROM K.B.

