

RECEIVED BY  
Form 3160-5  
(November 1983)  
(Formerly 9-331)  
DEC 10 1984

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

NM OIL CONS. COM. SECTION  
SUBMIT IN TRIPlicate  
Please follow instructions on re-  
lease, NM 88210

Expires August 31, 1985

6. LEASE DESIGNATION AND SERIAL NO.

NMA 38115

8. IF INDIAN, ALLOTTEE OR TRIBE NAME

N/A

7. UNIT AGREEMENT NAME

N/A

8. FARM OR LEASE NAME

Mike Federal Com.

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Pecos Slope Abo

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 12, T-8-S, R-25-E

12. COUNTY OR PARISH 13. STATE

Chaves

NM

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Stevens Operating Corporation

3. ADDRESS OF OPERATOR

P. O. Box 2203 Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)

At surface

660 FSL, 660 FWL, Sec. 12, T-8-S, R-25-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, WT, OR, etc.)

3548 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACURE TREAT

SHOOT OR ACIDIZING

REPAIR WELL

(Other)

PCLL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

10-11-84 TD @ 1:00 PM, 10-11-84 @ 4384'. Ran multishot shows bttm hole closure: 873.79' @ N78°, 47' 14" W.

10-12-84 Ran 110 jts 4 1/2 x 11.6# K-55 LTC csg set & cmnt @ 4384' w/370 sxs 50/50 POZ cmnt, 3# salt, 3/10 Halad-4, 1/4 FC. Plug dn @ 10:30 PM, 10-12-84.

10-22-84 Ran 1750' of 1" tbg between 8 5/8 & 4 1/2" csg & cmnt to surface w/425 sxs class "C" cmnt w/2% CaCl<sub>2</sub>. WOC 18 hrs. Pressure up 1000# for 30 minutes logging no pressure decrease.

10-28-84 Perf @ 3827', 28, 29, 30, 31, 32, 47, 48, 49, 50, 51, 52, 53, 54, (14 shots). Ran 120 jts 2 3/8" x 4# tbg w/4 1/2" Loc Set Pkr, spot 2 bbls 7 1/2% Abo acid over perfs. Pulled 5 jts, set Pkr @ 3703' (115 jts) & acidize w/3000 gals 7 1/2 HCL + 1000 SCF N<sub>2</sub>/bbl HCL & 21 Ball Sealers.

10-30-84 Kill well, pull tbg & Pkr out of hole. Frac w/40,000 gals, 75% quality foam. 42,000# 20/40 sand & 1800# 10/20 sand thru 4 1/2" casing.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Production Controller

DATE 11-05-84

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF

ACCEPTED FOR RECORD

TITLE

DATE

DEC 6 1984

\*See Instructions on Reverse Side