


STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.O.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

IL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501



Form C-103
Revised 10-1-73

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input checked="" type="checkbox"/>	CAS WELL <input type="checkbox"/>	OTHER <input type="checkbox"/>	7. Unit Agreement Name
Name of Operator Johnny F. Mobley <input checked="" type="checkbox"/>			8. Farm or Lease Name Mobley
Address of Operator P. O. Box 1443 Ruidoso, N.M. 88345			9. Well No. #1
Location of Well UNIT LETTER A 396 FEET FROM THE North LINE AND *30 FEET FROM THE East LINE, SECTION 29 TOWNSHIP 10S RANGE 28E NMPM.			10. Field and Pool, or Wildcat L.E. Ranch 22
11. Elevation (Show whether DF, RT, GR, etc.) 3,736.5 GR			12. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

FORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPERATIONS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
WORK ON OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3/28/84, 3:00 PM spud, set conduction and drill to 415'. 3/29/84 set 8 5/8 casing @ 2:00PM, ran 368' of 8 5/8, 24# surface casing. 1 regular guide shoe set 368'. Cemented W/160 sacks Class C w/2% calcium chloride. Circulate cement, bumped plug to 1,000PSI, released pressure and plug held okay. (Held 30 min. OK)
Drilled out 3/30/84 @ 2:00 PM. WOC 20 hours. Nippled up and tested to 1,000# for 30 minutes, okay. Reduced hole to 7 7/8". Drilled plug and resumed drilling. Total depth of 2,387' on 4/13/84 @ 11:30 PM, circulate and trip out. 4/14/84, 8:00 AM log well and perforated 2274-78, 2285-86, 2290-92, 2295-2300 with 2 shots per foot of size .40". No show of oil or gas. acidized all perms w/3000 g. 28% HCL. No show of oil or gas.

* Ran 2385' 4 1/2" 9.5# csg. Cmt'd, w/3000v. cmt. TUC @ 500'

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signature: <i>Johnny F. Mobley</i>	TITLE: operator	DATE: 5/18/84
Original Signed By Leticia A. Clements Supervisor District II		DATE: MAY 31 1984
CONDITIONS OF APPROVAL, IF ANY:		