IM OIL COMS. CO. TSION Drawer DD Artesia, NM 88210

5. LEASE

Form Approved. Budget Bureau No. 42-R1424

JUN 19 1984 DEPARTMENT FOR THE INTERIOR

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY		NM 19421-A 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)		NA 7. UNIT AGREEMENT NAME NA 8. FARM OR LEASE NAME
1. oil gas well well	☑ other	Hanagan A Federal 9. WELL NO.
2. NAME OF OPER		2 10. FIELD OR WILDCAT NAME
Stevens Operating Corporation 3. ADDRESS OF OPERATOR		Pecos Slope Abo
P. O. Box 2203 Roswell, NM 88201		11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 990 FWL 330 FSL, Sec 11,		AREA Sec. 11, T-7-S, R-26-E
AT SURFACE: T-7-S R-26-E		12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:		Chaves NM
AT TOTAL DEPTH:		14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:		TO THE WAY OF THE WORLD
		15. ELEVATIONS (SHOW DF, KDB, AND WD)
		3730.7 GR
TEST WATER SHUTFRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER COMPLETOR COM		(NOTE: Report results of multiple completion or zone change on Form 9–330.)
	POSED OR COMPLETED OPERATIONS (Clearly stated date of starting any proposed work. If well is true vertical depths for all markers and zones pertine	ent to this work.)*
5-25-84	Rig up pulling unit, Prep t	o perf.
5-26-84	Perforate @ 4415, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25 27, 28, 29, & 30 - (16 shots). Ran 135 jts. 2 3/8" x 4. tbg. & loc-set pkr. Spot 2 bbls. 7 1/2% HCL over perfs, pulled 4 jts, set pkr 4311' (131 jts-104' above top perf & acidize w/3000 gals. 7 1/2% HCL ± 1000 scf N2/bbls HC & 20 NCB.	
5-30-84	POH w/pkr & tbg. Rig up Do using 30,000 gals YF3 PSD (well & frac via 4 1/2" casing 33% CO2), 43,000# 20/40 sand.
5-31-84	Ran 132 jts. 2 3/8" x 4.7# Set @ 4347' (68' above top	tbg. & 4 1/2 Loc-Set packer. perf).
Subsurface Safety '	Valve: Manu. and Type	Set @ Ft.
18. I hereby certify	that the foregoing is true and correct	
SIGNED A	Timprod. Contr	Collerante 6-13-84
APPROVED BY P	ACCEPTED FOR RECORD (This space for Federal or State LIFR CHPSIE) PROVAL, IF ANY: JUN 18 1984	