



ALL OFF. COPIES GO TO
FEDERAL BUREAU OF
GEOL. SURV.

Form Approved.
Budget Bureau No. 42-R1424

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

Stevens Operating Corporation

3. ADDRESS OF OPERATOR

P. O. Box 2203, Roswell, NM 88201

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 990 FWL, 330 FSL, Sec. 11

AT SURFACE: T-7-S, R-26-E

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☐

5. LEASE

NM 19421-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hanagan A Federal

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

Pecos Slope Abo

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 11, T-7-S, R-26-E

12. COUNTY OR PARISH

Chaves

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3730.7 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.1)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-8-84 Trip out w/Pkr rig up dresser & perf. I SPF @ 4167 68, 69½, 70, 70½, 71, 71½, 72, 73-4302 02½, 03, 03½, 04-4322 22½, 23, 23½, 24-4338½ 39, 39½, 40 & 40½ (25-0.40 holes). Ran RBP (Loc set & Model "R") pkr plus 133 jts 2 3/8 x 4.7# tbg. set RBP @ 4391' & test (2000#) spot 4 bbls 7½% HCL @ 4358. Pulled 10 jts set pkr @ 4064 (123 jts) & acidiz w/5000 gals 7½% HCL plus 1000 SCF N₂/bbls.

6-12-84 Trip out w/Model "R" pkr & 123 jts 2 3/8" tbg. Rig up frac head & frac via 4½ casing w/60,000 gals YF4 PSD (33% CO₂), 86,000# 20/40 sand & 52,000# 10/20 sand.

6-13-84 Trip in w/tbg & wash over RBP. Pull RBP & ran tbg open ended set @ 4374.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Prod. Controller DATE 7-2-84

ACCEPTED FOR RECORD (This space for Federal or State office use)

APPROVED BY PETER W. CHESTER
CONDITIONS OF APPROVAL, IF ANY

TITLE

DATE

JUL 10 1984