

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Oil Cons.
N.M. DIV-Dist. 2
1301 W. Grand Avenue
Artesia, NM 88210

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☐ Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

Petroleum Development Corporation

3. Address and Telephone No.

4113 Eubank NE, Suite 400, Albuquerque, NM (505) 293-4044

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL 660' FWL S3, T7S, R26E

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Isler Pennzoil Fed. #3

9. API Well No.

30-005-62154

10. Field and Pool, or Exploratory Area

Undesignated Abo

11. County or Parish, State

Chaves County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☒ Notice of Intent

☐ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Start work approx. 2/13/2002

2. MIRUPU, bleed well down, ND wellhead, NU BOP

3. Plug #1 set @ 4419' - 4091' w/20 sks "C" + 2% CaCl₂, displace w/2 bbls fresh H₂O and 13.8 bbls 9# gelled H₂O - TAG

4. Plug #2 set @ 2770' - 2606' w/10 sks "C" + 2% CaCl₂, displace w/2 bbls fresh H₂O and 8 bbls 9# gelled H₂O 900' - 736'

5. Plug #3 set @ 841' - 677' w/10 sks "C" + 2% CaCl₂, displace w/1 bbl fresh H₂O and 1.6 bbls 9# gelled H₂O

6. Plug #4 set at surface w/10 sks "C" + 2% CaCl₂

7. Install dry hole marker

Please refer to attachment for complete job procedure and pertinent data.

At plug #2 need to perf @ 2770' + 8500'

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

14. I hereby certify that the foregoing is true and correct

Signed

Title Production Manager

Date 2/7/2002

(This space for Federal or State office use)

Approved by

Title P.E.

Date 2/12/02

Conditions of approval, if any:

Title 18
or repre

Accepted for record

only FEB 13 2002

willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements

Instruction on Reverse Side

RECEIVED

2006 FEB 11 7:10:34

SUPPLY CHAIN
INFORMATION