


NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	☒
FILE	☒
U.S.G.S.	☒
LAND OFFICE	☒
OPERATOR	☒

NEW MEXICO OIL CONSERVATION COMMISSION

30-005-6215



Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease

State ☒ Fee ☐

5. State Oil & Gas Lease No.

L-6276

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR RE-DRILL OR PLUG BACK TO A DIFFERENT RESERVOIR.
SEE APPLICATION FOR PERMIT AND FORM C-101 FOR SUCH PROPOSALS.

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER	7. Unit Agreement Name Campbell Station Unit
2. Name of Operator CARL A. SCHELLINGER	8. Farm or Lease Name Campbell Station Unit
3. Address of Operator P.O. Box 447, Roswell, New Mexico 88201	9. Well No. 4
4. Location of Well UNIT LETTER <u>G</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>4</u> TOWNSHIP <u>9</u> South RANGE <u>27</u> East NMPL.	10. Field and Pool, or Wildcat Wildcat Fusselman
11. Elevation (Show whether DF, RT, GR, etc.) 3842GR, 3853KB	12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☒	OTHER ☒ Perf and Test

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 8/2/84: Perforated Montoya 6616-6622, 6630-6632, 6634-6640 with 4 SPF, Acidized with 500 gal. 15% MCA, Swabbed Acid Water plus 91 BFW, Could not swab dry, GSG; 72 hr. SIBHP 2594#. Swabbed 40 BFW, 4 hrs.
- 8/8/84 Set Cast Iron BP @ 6600', Perforated Montoya 6526-6530 w/2 SPF; Acidized 3000 gal. 15% MCA; Swabbed acid water and swabbed @ rate of 1.5 to 2 BFWPH, Sli Show of Gas.
- 8/17/84 Set Cast Iron BP @ 6500' with 2 Bailers of Cement. Perforated Pennsylvanian 6243-6248, 6321-6327 with 2 SPF; Acidized 2000 gal. 15% MCA, Swabbed Load water with good show of gas. 12 hr. SITP 2000 psi.
- 8/22/84 Frac Penn Perfs 6243-6327 with 21000 gal. Pur-Gel 2% KCL plus 10,000 gal. CO₂ with 36,000# 20/40 sand.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Carl Schellinger TITLE Operator DATE 9/7/84

Original Signed By
Mike Williams

SEP 18 1984

APPROVED BY Oil & Gas Inspector

TITLE DATE

CONDITIONS OF APPROVAL, IF ANY: