

Operator Dale Nichols
 Well Lynx #1
 Unit G Section 19 Township 8 Range 29
 API # 30 -- 005 -- 62160

FOPS

Gates	850
San Andres	2052
Glorieta	3296
Wolfcamp	6174
Fusselman	6849
Tubb	4708'
Abc	5413'
Carson	6604'

* Well File shows no Attempt to
 Recover Fish @ 6402'

← Perf casing strings @ 60' - CMC
 Cast up 8 5/8" & 5 1/2" Annulus
 0-60'

- Salt gel mud consisting of 10# brine with 25# of gel per barrel must be placed between each plug
- Install Dry Hole Marker

Notify OCD 24 hrs. prior to any work done

← 100' Plug in 8 5/8" 312'-462' TAG
 ← Perf Both csg strings - 8 5/8" & 5 1/2" Annulus 312'-462'
 ← Perf csg @ 900' - 8 5/8" & 5 1/2" Annulus 800' to 900'

← 100' Plug inside Pipe 2075' to 2175' TAG
 ← Perf csg @ 2175' - 8 5/8" & 5 1/2" Annulus 2075' to 2175'

← Perf csg @ 3346' - Place 100' Plug From 3296'-3346' Inside Pipe -
 Place 100' Plug in 8 5/8" & 5 1/2" Annulus 3296' - 3346'

← 100' Plug 5227'-5327' TAG

← 100' Plug 6124'-6224' TAG
 ← 100' Plug 6700' to 6800' TAG OR CTBP @ 6800' by 35' on 4'

13 3/8
Circ
4 1/2
1400' TAG
EST.

8 5/8
2125'
300 SX
12" hole

5277'
TAG
1200 SX
9 7/8 hole

6350'
6350'
5 1/2
7491'
9 7/8