

NEW MEXICO OIL CONSERVATION COMMISSION  
DRAWER 110  
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>McKay Oil Co</u>		Lease <u>Bervendo</u>		Well # <u>14</u>	
Location of Well	Unit <u>I</u>	Section <u>10</u>	Township <u>10</u>	Range <u>24</u>	County
Drilling Contractor			Type of Equipment		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>12 1/4</u>	<u>8 5/8</u>	<u># 20</u>		<u>800</u>	

Casing Data:

Surface 14 joints of 15 inch 20 # Grade  

  (Approved) (Rejected)

Inspected by   date 5-25-84

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required  

Type of Shoe used   Float collar used   Btm 3 jts welded  

TD of hole 775 Set 730 Feet of 15 Inch 20 # Grade  

New-used csg. @   with   sacks neat cement around shoe

+ 25 sax   additives

Plug down @ 7100 (AM) (PM) Date 5-25-84

Cement circulated NO No. of Sacks  

Cemented by Western Witnessed by B.W. Reader

Temp. Survey ran @ 1:00 (AM) (PM) Date 5-25-84 top cement @ 170

Casing test @   (AM) (PM) Date  

Method Used   Witnessed by  

Checked for shut off @   (AM) (PM) Date  

Method used   Witnessed by  

Remarks:  

Ran 1" to 200 Ft and Circulated Cement with 110 SF Class C 4 1/2 CC