

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.O.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

RECEIVED BY

JUN 26 1984

5a. Indicate Type of Lease

State ☐

Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

O. C. D.

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

ARTESIA, OFFICE

OIL WELL ☒

GAS WELL ☐

OTHER-

Name of Operator

Yates Petroleum Corporation

Address of Operator

207 South 4th St., Artesia, NM 88210

Location of Well

UNIT LETTER N 660 FEET FROM THE South LINE AND 1980 FEET FROM
THE West LINE, SECTION 8 TOWNSHIP 8S RANGE 26E NMPM.

7. Unit Agreement Name

8. Farm or Lease Name

Byers ZV

9. Well No.

1

10. Field and Pool, or Wildcat

Wildcat

15. Elevation (Show whether DF, RT, GR, etc.)

3699' GR

12. County

Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPNS. ☒

PLUG AND ABANDONMENT ☐

WELL OR ALTER CASING ☐

CHANGE PLANS ☐

CASING TEST AND CEMENT JOB ☒

OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded 14-3/4" hole 11:30 PM 6-18-84. Lost returns at 905', dry drill to 1015'. Ran 24 jts of 10-3/4" 40.5# J-55 ST&C casing set 1015'. 1-Texas Pattern notched guide shoe set 1015'. Insert float set 974'. Cemented w/400 sacks Howco Lite, 1/4# celloseal and 3% CaCl2. Tailed in w/150 sacks Class "C" 2% CaCl2. Compressive strength of cement - 1250 psi in 12 hrs. PD 6:00 PM 6-20-84. Bumped plug to 1000 psi, released pressure and float held okay. Cement circulated 45 sacks. WOC. Drilled out 12:00 noon 6-21-84. WOC 18 hrs. Nipped up and tested to 1000 psi for 30 minutes, OK. Reduced hole to 7-7/8". Drilled plug and resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

CHD Leslie A. Clements

TITLE Production Supervisor

DATE 6-25-84

Original Signed By

Leslie A. Clements

Supervisor District II

PROVED BY _____

TITLE _____

DATE JUN 25 1984

CONDITIONS OF APPROVAL, IF ANY: