

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	<input checked="" type="checkbox"/>
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED BY
JUL 16 1984
O. C. D.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name	
J. P. White D	
9. Well No.	
11	
10. Field and Pool, or Wildcat	
Race Track SA	
12. County	
Chaves	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
2. Name of Operator Cibola Energy Corporation
3. Address of Operator P. O. Box 1668, Albuquerque, New Mexico 87103
4. Location of Well UNIT LETTER M 990 FEET FROM THE North LINE AND 330 FEET FROM THE West LINE, SECTION 20 TOWNSHIP 10S RANGE 28E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3750 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7-10-84 Spudded well at 7:00 pm. Ran 337' 8 5/8" 23# casing, texas pattern guide shoe and insert float. Cemented with 346 sx Class C Cement with 2% CaCl2. Circulate 20 sacks to surface. Bump plug to 750#. Held pressure 30 minutes. WOC 18 hrs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Karen Azar</u>	TITLE <u>Drilling Secretary</u>	DATE <u>7-13-84</u>
APPROVED BY <u>Original Signed By</u>	TITLE <u>Supervisor District II</u>	DATE <u>JUL 17 1984</u>
CONDITIONS OF APPROVAL, IF ANY:		