

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

# OIL CONSERVATION DIVISION

P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

MAR - 5 1992

O. C. D.

WELL API NO.

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Smith Fee

8. Well No.

No. 1

9. Pool name or Wildcat

Pecos Slope

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL  
WELL ☐

GAS  
WELL ☒

OTHER P & A

2. Name of Operator

McClellan Oil Corporation

3. Address of Operator

P O Drawer 730, Roswell, NM 88202-0730

4. Well Location

Unit Letter D : 660 Feet From The North Line and 1200 Feet From The West Line

Section 27

Township 6 South

Range 27 East

NMPM

Chaves

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☒

OTHER: ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to P & A as follows:

35ft on CIBP at 4970 ft 35f

1. Set C.I.B.P. at 4700' & put 30' cmt. on top.

2. Shoot off 4 1/2" casing at 3700' & pull out of hole.

3. 1st Plug 3750' to 3650' 30 sx. Stub Plug Tag

2nd Plug 2550-2535' to 3435' 2430 30 sx.

3rd Plug 1450' to 1350' 1300 35 sx. Tag top of cement.

4th Plug 60' to Surface 25 sx.

All cement plugs are to be Class "C", 2% CaCl.

4. All plugs will have heavy mud between them.

5. Will install dry hole marker.

8 5/8 csg. - 1400' Circulated  
T.O.C. - 3800' (4 1/2 & 7 7/8" hole)  
Perfs - 4742- 4891' 20 holes

Plugging

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Mitch Lee

TITLE

Drilling & Compl. Engineer

DATE

TYPE OR PRINT NAME

Mitch Lee

TELEPHONE NO.

622-3200

(This space for State Use)

APPROVED BY

GW

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

XXXXXX

Surf - Plug

Gal Between  
All Plugs

Yates 342

Queen 922

Plug 1450 - 1300 Tag

San Andres 1355

XXXXXX

8 5/8 1400 ft cir

XXXXXX

Plug 2550 - 2430

Glorieta 2485

Yaso 2538

XXXXXX

3700 stub Plug  
50 ft in 50 ft out - Tag

Tubb 3943

XXXXXX

CIBP 4700 35 ft cement

Perfs 4742 - 4891

XXXXXX

CIBP 35 ft cement

Perfs 4987 - 4999

Perfs 5073 - 77

Abo 4858

970 -  
sandy  
no  
end of  
vent

4 1/2 5108

Temp Survey TOC 3800