


NO. OF COPIES RECEIVED	
DISTRIBUTION	
ALTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
J.S.G.S.	<input checked="" type="checkbox"/>
LAND OFFICE	<input checked="" type="checkbox"/>
OPERATOR	<input checked="" type="checkbox"/>

N MEXICO OIL CONSERVATION COMMISSIO



Supersedes Old
C-102 and C-103
Effective 1-1-81

5a. Indicate Type of Lease	State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name Sallie	
9. Well No. 2	
10. Field and Pool, or Wildcat Und LE Ranch SA	
12. County Chaves	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

Name of Operator
Cibola Energy Corporation ✓

Address of Operator
P. O. Box 1668, Albuquerque, New Mexico 87103

Location of Well
UNIT LETTER I 1980 FEET FROM THE South LINE AND 660 FEET FROM
THE East LINE, SECTION 30 TOWNSHIP 10S RANGE 28E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3724.9

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
SUBSEQUENT REPORT OF:

NOTICE OF INTENTION TO:			
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10-26-84
Ran 330' 8 5/8" 23# casing, texas pattern guide shoe and insert float. Cemented with 200 sacks Class "C" cement with 3% CaCl.
Cement circulated but fell approximately 75' after job was completed.
Bump plug to 750#. Held pressure 30 minutes. Filled annulus with redi-mix cement. WOC 18 hours.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Karen Azar TITLE Drilling Secretary DATE 10-29-84

APPROVED BY Leslie A. Clements TITLE Supervisor District II DATE OCT 30 1984

CONDITIONS OF APPROVAL, IF ANY: