

STAFF	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
DISG.	<input checked="" type="checkbox"/>
LAND OFFICE	<input type="checkbox"/>
OPERATOR	<input checked="" type="checkbox"/>

NEW MEXICO OIL COM.

RECEIVED BY

DEC 26 1984

O. C. D.

ARTESIA, OFFICE

1. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
2. State Oil & Gas Lease No.	

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Cibola Energy Corporation		8. Farm or Lease Name CX Plains
3. Address of Operator P. O. Box 1668, Albuquerque, New Mexico 87103		9. Well No. 11
4. Location of Well UNIT LETTER <u>P</u> <u>970</u> FEET FROM THE <u>South</u> LINE AND <u>990</u> FEET FROM THE <u>East</u> LINE, SECTION <u>19</u> TOWNSHIP <u>10S</u> RANGE <u>28E</u> NMPM.		10. Field and Pool, or Wildcat Race Track SA
15. Elevation (Show whether DF, RT, GR, etc.) 3758		12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12-19-84 Ran 308' 8 5/8" 23# casing, texas pattern guide shoe and insert float. Cemented with 200 sx Class C cement with 2% CaCl. Circulate approximately 50 sx to pit. Bump plug with 750#. Held pressure 30 minutes. Top of cement fell 30'. Wait 1 hr. Fill annulus with cement. WOC 18 hrs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Karen Azar TITLE Drilling Secretary DATE 12-20-84

APPROVED BY Original Signed By Leslie A. Clements TITLE Supervisor District II DATE DEC 28 1984  
CONDITIONS OF APPROVAL, IF ANY: