

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE	<input checked="" type="checkbox"/>	
FILE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
U.S.G.S.		
LAND OFFICE	<input checked="" type="checkbox"/>	
OPERATOR	<input checked="" type="checkbox"/>	

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED BY

NOV 30 1984

O. C. D.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. L-2464		

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator
McClellan Oil Corporation

3. Address of Operator
P.O. Drawer 730, Roswell, NM 88201

4. Location of Well
UNIT LETTER F, 1980 FEET FROM THE North LINE AND 1650 FEET FROM
West LINE, SECTION 36 TOWNSHIP 9-S RANGE 25-E NMPM.

7. Unit Agreement Name
8. Farm or Lease Name Tolmac State
9. Well No. 4
10. Field and Pool, or Wildcat South Pecos Slope Abo
12. County Chaves

15. Elevation (Show whether DF, RT, GR, etc.)
3622' G.L.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11/20/84: Spudded well with 12-1/4" bit. Drilled to 1100'. Set 1050' of 8-5/8" 24# K-55. Cemented with 400 sx Pacesetter Lite and 200 sx Class "C" 2% CaCl. Circulated 50 sx. Nippled up BOP's. Test 1000 psi for 30 min. WOC - 18 hours. Drilling out with 7-7/8" bit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED _____ TITLE Drilling Engineer DATE 11/29/84

Original Signed By
Leslie A. Clements
Supervisor District 4F

APPROVED BY _____

DATE DEC 11 1984

CONDITIONS OF APPROVAL, IF ANY: