

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE	✓	
FILE	✓	✓
U.S.G.S.		
LAND OFFICE		
OPERATOR	✓	

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED BY

NOV 30 1984

O. C. D.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
L-2464	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	2. Name of Operator McClellan Oil Corporation ✓
3. Address of Operator P.O. Drawer 730, Roswell, NM 88201	4. Location of Well UNIT LETTER <u>F</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1650</u> FEET FROM THE <u>West</u> LINE, SECTION <u>36</u> TOWNSHIP <u>9-S</u> RANGE <u>25-E</u> NMPM.

7. Unit Agreement Name
8. Farm or Lease Name Tolmac State
9. Well No. 4
10. Field and Pool, or Wildcat South Pecos Slope Abo
12. County Chaves

15. Elevation (Show whether DF, RT, GR, etc.)
3622' G.L.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11/28/84: TD well at 4420'. Prep to log. Ran log using Schlumberger CNL-LDT-DLL.

11/29/84: Ran 109 joints of 4-1/2" 10.5# casing to 4358.81'. Cemented well using 1000 gals. Flochek-21 ahead mud flush then 350 sx 50/50 poz "C", .2% CFR-2, .2% Hallad 4, 6# salt. PBD - 4297'. TOC - 3200'.

11/29/84: Released rig.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Mike Williams TITLE Drilling Engineer DATE 11/29/84

APPROVED BY Mike Williams TITLE Oil & Gas Inspector DATE DEC 11 1984

CONDITIONS OF APPROVAL, IF ANY: