

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Exp. 5-6-85

Operator <u>Sanders Oil & Gas.</u>		Lease <u>Roswell</u>		Well # <u>1</u>	
Location of Well	Unit <u>J</u>	Section <u>29</u>	Township <u>10 S</u>	Range <u>25 E</u>	County <u>Chaves</u>
Drilling Contractor	<u>N/A</u>		Type of Equipment <u>Rotary</u>		

* = CSG. TO WITNESS

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cemen
* 14 3/4"	10 3/4"	40.5 #	NEW	800	CIRC.
12 1/4"	8 5/8"	24.0 #	"	1300	370
7 7/8"	4 1/2"	9.5 #	"	4500	675

Casing Data:

Surface _____ joints of _____ inch _____ # Grade _____
(Approved) (Rejected) _____

Inspected by _____ date _____

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required 500

Type of Shoe used TYPE M NOTCHED Float collar used YES Btm 3 jts welded YES

TD of hole 940 Set 940 Feet of 8 5/8 Inch 24 # Grade 1-55

New used csg. @ 940 with 150 sacks neat cement around shoe C.I.C 2 1/2

+ 350 sax HOWCO LIVE additives 2% CACl₂

Plug down @ 4:15 (AM) (PM) Date 10/28/85

Cement circulated YES No. of Sacks 82 SXS

Cemented by HALLIBURTON Witnessed by Darryl Brooks

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____

