

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Artesia, NM 88210

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR ARCO Oil and Gas Company
Division of Atlantic Richfield Company

3. ADDRESS OF OPERATOR
P. O. Box 1710, Hobbs, New Mexico 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FNL & 660' FEL (Unit A)
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

(other)

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐

Spud, Run & Cmt
Surface Csg.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Set 14" conductor pipe @ 30' & cmt'd w/3 yds Redi-mix to surface. Spudded 12 1/4" hole @ 4:00 AM 12/26/84. Finished drlg 12 1/4" hole to 1163' @ 5:00 PM 12/28/84. RIH w/ 8-5/8" OD 24# K-55 csg, set @ 1163'. Cmt'd 8-5/8" csg w/100 sx Thick-set cmt cont'g 4% CaCl₂, 10#/sk Gilsonite, 1/2#/sk flocele, 300 sx HOWCO Lite cmt cont'g 2% CaCl₂, 1/2#/sk flocele, followed by 200 sx Cl C cmt cont'g 2% CaCl₂. Did not circ. PD @ 10:45 AM 12/29/84. WOC 6 hrs. Ran temp survey. Temp survey indicated TOC @ 310'. Ran 1" tbg & pmpd 200 sx Cl C Neat cont'g 2% CaCl₂. WOC 3 hrs. Tagged TOC @ 230'. Pmpd 200 sx Cl C cmt cont'g 3% CaCl₂. WOC 3 hrs. Tagged TOC @ 75' ES. Pmpd 100 sx Cl C Neat cmt to surf. Cmt circ @ 2:00 AM 12/30/84. Cut off csg & welded on wellhead. NU BOP. Pressure tested csg to 1250# for 30 mins OK.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED E. G. Bush TITLE Drlg Engr. DATE 1/03/85

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF

ACCEPTED FOR RECORD

PETER W. CHESTER

JAN 17 1985

TITLE

DATE