Form 3160-5 (June 1990)

1. Type of Well

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

OFERATOR'S COPY

0197 FORM APPROVED Budget Bureau No. 1004-0135

Expires: March 31, 1993 5. Lease Designation and Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

Oil S Gas Other	The state of the s	8. Well Name and No.
2. Name of Operator	/8°	Mary K #1
Petroleum Development Corporat 3. Address and Telephone No.	ion (a) (a) (b) (c) (c) (c) (c) (c) (c) (c) (c) (c) (c	9. API Well No. 30-005-62232
4113 Fuhank NE, Suite 400, Alb 4 Location of Well (Footage, Sec., T., R., M., or Survey De	uquerque, NM 87114 (505) 293-4044	10. Field and Pool, or Exploratory Area
660' FNL 775' FWL S29, T10S		11. County or Parish, State
		Chaves County, NM
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, RI	EPORT, OR OTHER DATA
	TYPE OF ACTION	
TYPE OF SUBMISSION	TYPE OF AC	TION
TYPE OF SUBMISSION Notice of Intent	Abandonment	Change of Plans
	Abandonment Recompletion Plugging Back	
Notice of Intent	Abandonment Recompletion Plugging Back Casing Repair Altering Casing	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection
Notice of Intent Subsequent Report Final Abandonment Notice	Abandonment Recompletion Plugging Back Casing Repair	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

- 1. Start work approx. 2/14/2002
- 2. MIRUPU, bleed well down, ND wellhead, NU BOP
- 3. Circulate casing w/9# gelled H20
- 4. Plug #1 set @ 3898' 3324' w/35 sks "C" + 2% CaCl2, displace w/2 bbls fresh H2O and 10.8bbls 9# gelled H2O
- 5. Plug #2 set @ 1280'- 1116' w/10 sks "C" + 2% CaC12, displace w/2 bbls fresh H2O and 2.3 bbls 9# gelled H2O
- 6. Plug #3 set @ 767'- 607' w/10 sks "C" + 2% CaC12, displace w/1 bb1 fresh H2O and 1.3 bbls 9# gelled H20
- 7. Plug #4 set @ surface w/10 sks "C" + 2% CaC12
- 8. Install dry hole marker

Please refer to attachment for complete job procedure and pertinent data.

14. I hereby certify the	it the foregoing is true and correct	Tide Production Manager	Date2/7/2002
(This space for Fed Approved by Con	ieral or State office use)	Title	Date
-	ted for record		
FEB 13 2002		willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements a instruction on Reverse Side	

SCHERE CHAEL STREET STR