

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>YPC</u>		Lease <u>Bobcat ABT St.</u>		Well # <u>1</u>	
Location of Well	Unit <u>M</u>	Section <u>36</u>	Township <u>8S</u>	Range <u>25E</u>	County <u>Chaves</u>
Drilling Contractor	<u>L&M #2</u>		Type of Equipment <u>Rotary</u>		

* = CSG. TO WITNESS

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cemen
* 12 1/4	8 5/8	24	1000 NEW	1000'	800 (circ)
7 7/8	4 1/2	9.5	TD NEW	TD	250

Casing Data:

Surface 28 joints of 8 5/8 inch 24 # Grade J-55

Yes

(Approved) (Rejected)

Inspected by BW Weaver date 1-22-85

Cementing Program

Size of hole 12 1/4 Size of Casing 8 5/8 Sacks cement required 150

Type of Shoe used Tex-Ar Float collar used Insert Btm 3 jts welded Yes

TD of hole 917 Set 923 Feet of 8 5/8 Inch 24 # Grade J-55

New-used csg. @ 923 with 150 sacks neat cement around shoe

+ 400 sax Pac-Lite etc additives 3% CC

Plug down @ 7:00 (AM) (PM) Date 1-23-85

Cement circulated yes No. of Sacks 130

Cemented by Western Witnessed by BW Weaver

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: