

DISTRICT I

State of New Mexico  
Energy, Minerals and Natural Resources Department

P.O. Box 1980, Hobbs NM 88240

DISTRICT II

P.O. Drawer DD, Artesia NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL GAS  
WELL ☒ WELL ☐ OTHER ☐

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 South 4th., Artesia, NM 88210

4. Well Location

Unit Letter P 990 Feet From The SOUTH Line and 990 Feet From The EAST Line

Section 25 Township 10S Range 26E NMPM CHAVES COUNTY

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3694' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

3-21-02 - MIRU PU; NU BOP. TOH w/ tubing & packer - packer was not set. TIH w/ tubing, tagged @ 735'. Circ hole. Started circulating out 8-5/8" casing. TOH & TIH w/ packer - set @ 560'. Tested 4-1/2" casing to 500 psi for 5 min, held OK. Called Van Burton w/ OCD to see if we can circ cement to surface - he said that would work. TOH laying tubing down.

3-22-02 - RU DS on 4-1/2" casing; broke circulation up 8-5/8" casing. Pumped 250 sx "C" Neat cement. Did not get cement to surface; had good returns. Displaced cement to 500'. Shut down. Prep to TIH w/ tubing & tag cement.

3-24-02 - TIH w/ tubing & tag cement @ 330'. TOH & RU wireline. TIH w/ 3-3/8" casing gun - perf @ 310'. TOH & lay down tubing. RU DS on casing; circ cement down 4-1/2" & up 8-5/8". Shut well in. RD DS. RD pulling unit.

Installed regulation dry hoe marker - PLUGGED & ABANDONED.

I hereby certify that the information above is a true and complete to the best of my knowledge and belief

SIGNATURE

*Henna J. Clark*  
DONNA J. CLARK

TITLE

Operations Technician

DATE

2/27/02

TYPE OR PRINT NAME

TELEPHONE NO.

505-748-1471

(This space for State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APR 24 2002