		Supersedes Uld
DISTRIBUTION		C-102 and C-103
ANTA FE W MEXICO OIL CONSER	ATION COMPANYEL BY	Effective 14-65
J.S.G.S.		5a. Indicate Type of Lease
AND OFFICE	MAY 3 1 1985	State Fee X
PERATOR		5. State Oil & Gas Lease No.
	O. C. D.	
SUNDRY NOTICES AND REPORTS ON WI (DO NOT USE THIS FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK USE "APPLICATION FOR PERMIT		
		7. Unit Agreement Name
OIL A GAS OTHER-		
Name of Operator		8. Farm of Lease Name
Cibola Energy Corporation		Mona
Address of Operator		9. Well No.
P. O. Box 1668, Albuquerque, New Mexico	87103	2
Location of Well		10/Field and Pool, or Wildcat
C 330 FEET FROM THE North	2310	Race Track San Andres
UNIT LETTER JOU FEET FROM THEUUL LII	_ LINE AND PEET PHOM	
109	28F	
THE West LINE, SECTION 7 TOWNSHIP 105	RANGE ZOL HMPM.	
15. Elevation (Show whether DF	F. RT. GR. etc.)	12. County
		Chaves (
<u>1111111111111111111111111111111111111</u>		
6. Check Appropriate Box To Indicate Nat		
NOTICE OF INTENTION TO:	SUBSEQUENT	REPORT OF:
		
PERFORM REMEDIAL WORK	REMEDIAL WORK	ALTERING CASING
	COMMENCE DRILLING OPHS. X	PLUG AND ABANDONMENT
	CASING TEST AND CEMENT JOB 🔀	
	OTHER	

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 5-19-85 Spudded with rotary @11:00 am.
- 5-20-85 Ran 326' 8 5/8" 23# casing insert float and texas pattern guide shoe. Cemented with 225 sx Class C cement with 2% CaCl2. Circulated 80 sx to pit. Bump plug with 750#. Held pressure 30 minutes. WOC 18 hrs.

5-22-85 TD at 2360'.

5-23-85 Ran 2358' 4½" 9.5# casing, texas pattern guide shoe, and insert float. Cemented with 90 sx self stress cement with 2% CaCl2. Bump plug with 1000#. Held pressure 30 minutes. WOC 18 hrs.

8. I hereby certify that the information above is true and c	complete to the b	est of my knowledge and belief.	
Karen anger	TITLE	Drilling Secretary	May 28, 1985
	TITLE		JUN_04_1985
CONDITIONS OF APPROVAL, IF ANY		Supervisor District II	•