

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

Revised 3/25/86

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input type="checkbox"/> GAS <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Tenneco Oil Company	8. Farm or Lease Name Plains SL 19
3. Address of Operator 7990 IH 10 West, San Antonio, TX 78230	9. Well No. #1
4. Location of Well UNIT LETTER B 380 FEET FROM THE north LINE AND 2200 FEET FROM THE east LINE, SECTION 19 TOWNSHIP 10S RANGE 28E NMPM.	10. Field and Pool, or Wildcat Wildcat Devonian
15. Elevation (Show whether DF, RT, GR, etc.) GR 3760.4	12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input checked="" type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

- MIRU Pulling Unit
- Make sure well is dead. ND WH. NU BOP.
- Unset Otis perma-latch packer @6453' and POOH w/packer and Vann gun assembly.
- GIH w/ 2 3/8" tbg. open ended to ± 6680'.
- Spot 25 sks C1 'H' neat cement from ± 6680 -6500'.
- PU out of cement to ± 6400' and reverse out any excess. Circ. hole w/ 9.5 mud laden fluid.
- POOH to ± 5950'. Spot 25 sks C1 'H' neat cement from 5950 - 5770'. PU and reverse excess cement.
- POOH LD workstring. ND BOP. NU dry hole tree. RDMO.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Senior Production Engineer DATE March 14, 1986
APPROVED BY [Signature] TITLE OIL AND GAS INSPECTOR DATE APR 15 1986
CONDITIONS OF APPROVAL, IF ANY: