

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.O.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

5a. Indicate Type of Lease  
State ☐ Fee ☒  
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Unit Agreement Name
2. Name of Operator Cibola Energy Corporation	8. Farm or Lease Name Plains 6
3. Address of Operator P. O. Box 1668, Albuquerque, New Mexico 87103	9. Well No. 3
4. Location of Well UNIT LETTER N 990 South 2310 FEET FROM THE LINE AND FEET FROM West 6 10S 28E THE LINE, SECTION TOWNSHIP RANGE NMPM.	10. Field and Pool, or Wildcat Race Track San Andre
15. Elevation (Show whether DF, RT, GR, etc.) 3827.7	12. County Chaves

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:


PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1-22-86 Spudded with Rotary at 3:00 pm.

1-23-86 Ran 294' 8 5/8" casing, texas pattern guide shoe and insert float. Cemented with 200 sx Class C cement with 2% CaCl. Circulated 5 sx to pit. Bump plug with 750#. Held pressure 30 minutes. WOC 18 hrs.

1-27-86 TD well at 2330'.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Karen Azar TITLE Drilling Secretary DATE 1-28-86  
Original Signed By Les A. Clements  
APPROVED BY Supervisor District II TITLE  DATE JAN 31 1986  
CONDITIONS OF APPROVAL, IF ANY: