me, or farits attrives	OIL CONSERVATIO		Form C-103
DISTRIBUTION	P. O. BOX 208		Revised 10-1-78
BANTA PE	SANTA PE, NEW ME	⟨ico 8/7501	
FILE		े हैं। पूर्व	5a. Indicate Type of Lease
U.S.G.S.		and the state of t	State X Fee
LAND OFFICE			5. State Oil & Gas Lease No.
OPENATOR			5. State Off & Gds Lease No.
<u> </u>			
	ARTESA, CIET	E	
SUNDRY	NOTICES AND REPORTS ON WELL	A DIFFERENT RESERVOIR.	
USE "APPLICATIO	OSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO IN FOR PERMIT -" (FORM C-101) FOR SUCH PROP	OSALS.)	7. Unit Agreement Name
1.			7. Olli Agreement Italia
OIL X WELL .	OTHER-		
2. Name of Operator			8. Farm or Lease Name
	•	•	Chata DI 16
Tenneco Oil Comp	any		State RL 16
3. Address of Operator			3
7990 IH 10 West,	San Antonio, TX 78230		1
4. Location of Well			10. Field and Pool, or Wildcat
	20 couth	330	Wildcat-Devonian
UNIT LETTER	30 FEET FROM THE south LIN	IE AND FEET FROM	THIN THINKS
west	16 YOWNSHIP 11S	PANSE 28E	
THE LINE, SECTION	TOWNSHIP		
mmmmm	15. Elevation (Show whether DF, R	T. GR. etc.)	12. County
		,,,,	Chaves
	3669.5 GR		Cliaves
16. Check A	ppropriate Box To Indicate Nature	of Notice. Report of Ot	her Data
		SUBSECUEN	T REPORT OF:
NOTICE OF IN	TENTION TO:	308324021	. KEI OKT OI
			
PERFORM REMEDIAL WORK	PLUE AND ABANDON REM	EDIAL WORK	ALTERING CASING
	сом	MENCE DRILLING OPHS.	PLUG AND ABANDONMENT
TEMPORARILY ASANOON	CHANGE PLANS CASI	NG TEST AND CEMENT JOB	
PULL OR ALTER CABING			
	° اے	THER	
OTHER			
OTHER			in the state of th
17, Describe Proposed or Completed Op-	erations (Clearly state all pertinent details, a	nd give pertinent dates, includin	g estimated date of starting any proposed
17. Describe Proposed or Completed Op- work) SEE RULE 1103.	erations (Clearly state all pertinent details, a	nd give persinent dases, includin	g estimated date of starting any proposed
17. Describe Proposed or Completed Op- work) SEE RULE 1103.	erations (Clearly state all pertinent details, a	nd give persinens dases, includin	g estimated date of starting any proposed
work) SEE RULE 1103.		nd give persinens dases, includin	g estimated date of starting any proposed
Drilled 7 7/8"	hole to 7250'		
Drilled 7 7/8" Logged hole wit	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC	C P&A well with bala	nced cement plugs at
Drilled 7 7/8" Logged hole wit	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC	C P&A well with bala	nced cement plugs at
Drilled 7 7/8" Logged hole wit 7149', 6591' 50	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC 10', 2716', 1972' and 360'.	C P&A well with bala Set 10 sack plug a	nced cement plugs at t surface, welded
Drilled 7 7/8" Logged hole wit 7149', 6591' 50 plate over casi	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC	C P&A well with bala Set 10 sack plug a	nced cement plugs at t surface, welded
Drilled 7 7/8" Logged hole wit 7149', 6591' 50	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC 10', 2716', 1972' and 360'.	C P&A well with bala Set 10 sack plug a	nced cement plugs at t surface, welded
Drilled 7 7/8" Logged hole wit 7149', 6591' 50 plate over casi	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC 10', 2716', 1972' and 360'.	C P&A well with bala Set 10 sack plug a	nced cement plugs at t surface, welded
Drilled 7 7/8" Logged hole wit 7149', 6591' 50 plate over casi	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC 10', 2716', 1972' and 360'.	C P&A well with bala Set 10 sack plug a	nced cement plugs at t surface, welded
Drilled 7 7/8" Logged hole wit 7149', 6591' 50 plate over casi	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC 10', 2716', 1972' and 360'.	C P&A well with bala Set 10 sack plug a	nced cement plugs at t surface, welded at 10:00 a.m. on
Drilled 7 7/8" Logged hole wit 7149', 6591' 50 plate over casi	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC 10', 2716', 1972' and 360'.	C P&A well with bala Set 10 sack plug a	nced cement plugs at t surface, welded at 10:00 a.m. on
Drilled 7 7/8" Logged hole wit 7149', 6591' 50 plate over casi	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC 10', 2716', 1972' and 360'.	C P&A well with bala Set 10 sack plug a	nced cement plugs at t surface, welded at 10:00 a.m. on
Drilled 7 7/8" Logged hole wit 7149', 6591' 50 plate over casi	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC 10', 2716', 1972' and 360'.	C P&A well with bala Set 10 sack plug a	nced cement plugs at t surface, welded at 10:00 a.m. on
Drilled 7 7/8" Logged hole wit 7149', 6591' 50 plate over casi	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC 10', 2716', 1972' and 360'.	C P&A well with bala Set 10 sack plug a	nced cement plugs at t surface, welded at 10:00 a.m. on
Drilled 7 7/8" Logged hole wit 7149', 6591' 50 plate over casi	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC 10', 2716', 1972' and 360'.	C P&A well with bala Set 10 sack plug a	nced cement plugs at t surface, welded
Drilled 7 7/8" Logged hole wit 7149', 6591' 50 plate over casi	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC 10', 2716', 1972' and 360'.	C P&A well with bala Set 10 sack plug a	nced cement plugs at t surface, welded at 10:00 a.m. on
Drilled 7 7/8" Logged hole wit 7149', 6591' 50 plate over casi	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC 10', 2716', 1972' and 360'.	C P&A well with bala Set 10 sack plug a	nced cement plugs at t surface, welded at 10:00 a.m. on
Drilled 7 7/8" Logged hole wit 7149', 6591' 50 plate over casi	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC 10', 2716', 1972' and 360'.	C P&A well with bala Set 10 sack plug a	nced cement plugs at t surface, welded at 10:00 a.m. on
Drilled 7 7/8" Logged hole wit 7149', 6591' 50 plate over casi	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC 10', 2716', 1972' and 360'.	C P&A well with bala Set 10 sack plug a	nced cement plugs at t surface, welded at 10:00 a.m. on
Drilled 7 7/8" Logged hole wit 7149', 6591' 50 plate over casi	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC 10', 2716', 1972' and 360'.	C P&A well with bala Set 10 sack plug a	nced cement plugs at t surface, welded at 10:00 a.m. on
Drilled 7 7/8" Logged hole wit 7149', 6591' 50 plate over casi	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC 10', 2716', 1972' and 360'.	C P&A well with bala Set 10 sack plug a	nced cement plugs at t surface, welded at 10:00 a.m. on
Drilled 7 7/8" Logged hole wit 7149', 6591' 50 plate over casi	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC 10', 2716', 1972' and 360'.	C P&A well with bala Set 10 sack plug a	nced cement plugs at t surface, welded at 10:00 a.m. on
Drilled 7 7/8" Logged hole wit 7149', 6591' 50 plate over casi 12/23/85	hole to 7250' h GR-MSFL-DLL and GR-CNL-FD0 10', 2716', 1972' and 360'. ng and installed dryhole man	C P&A well with bala Set 10 sack plug a cker. Rig released	nced cement plugs at t surface, welded at 10:00 a.m. on
Drilled 7 7/8" Logged hole wit 7149', 6591' 50 plate over casi 12/23/85	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC 10', 2716', 1972' and 360'.	C P&A well with bala Set 10 sack plug a cker. Rig released	nced cement plugs at t surface, welded at 10:00 a.m. on
Drilled 7 7/8" Logged hole wit 7149', 6591' 50 plate over casi 12/23/85	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC 10', 2716', 1972' and 360'. ng and installed dryhole man	C P&A well with balaneset 10 sack plug acker. Rig released with the sack plug acker. Rig released with the sack plug acker.	nced cement plugs at t surface, welded at 10:00 a.m. on
Drilled 7 7/8" Logged hole wit 7149', 6591' 50 plate over casi 12/23/85	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC 10', 2716', 1972' and 360'. ng and installed dryhole man	C P&A well with balaneset 10 sack plug acker. Rig released with the sack plug acker. Rig released with the sack plug acker.	nced cement plugs at t surface, welded at 10:00 a.m. on
Drilled 7 7/8" Logged hole wit 7149', 6591' 50 plate over casi 12/23/85	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC 10', 2716', 1972' and 360'. ng and installed dryhole man	C P&A well with bala Set 10 sack plug a cker. Rig released	nced cement plugs at t surface, welded at 10:00 a.m. on
Drilled 7 7/8" Logged hole wit 7149', 6591' 50 plate over casi 12/23/85	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC 10', 2716', 1972' and 360'. ng and installed dryhole man	C P&A well with balaneset 10 sack plug acker. Rig released with the sack plug acker. Rig released with the sack plug acker.	nced cement plugs at t surface, welded at 10:00 a.m. on
Drilled 7 7/8" Logged hole wit 7149', 6591' 50 plate over casi 12/23/85	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC 10', 2716', 1972' and 360'. ng and installed dryhole man	P&A well with balance Set 10 sack plug and ker. Rig released who well and belief.	nced cement plugs at t surface, welded at 10:00 a.m. on
Drilled 7 7/8" Logged hole wit 7149', 6591' 50 plate over casi 12/23/85	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC 10', 2716', 1972' and 360'. ng and installed dryhole man	P&A well with balance Set 10 sack plug and ker. Rig released who well and belief.	nced cement plugs at t surface, welded at 10:00 a.m. on
Drilled 7 7/8" Logged hole wit 7149', 6591' 50 plate over casi 12/23/85	hole to 7250' h GR-MSFL-DLL and GR-CNL-FDC 10', 2716', 1972' and 360'. ng and installed dryhole man	C P&A well with balaneset 10 sack plug acker. Rig released with the sack plug acker. Rig released with the sack plug acker.	nced cement plugs at t surface, welded at 10:00 a.m. on

STATE OF NEW MEXICO
IGY AND MINERALS DEPARTMENT

STATE OF NEW			PERTURNIE	D DV								
RGY AND MINERAL		7 1	RECEIVE						ſ	-		e of Leuse
DISTRIBUTION		┤ 	JAN-20	100c ^{P.}	о, врх	2088			-		X	Fee L
SANTA FE										5. State	O11 & G	as Lease No.
FILE	VV		COMPLET ARTESIA, C	n				DODT AND	21.00			
U.S.G.S.		- WELL	COMPLET	ION OR	RECON	APLETIO	NKE	PURTANI			11111	
OPERATOR		- L	AKIESIM, C	JI FICE						7///	77777	71111111
TYPE OF WELL	BASM									7. Unit	Agreeme	nt Name
	A. 14.	oir 🗀	GAS WELL	٦	DRY X	OTHER_			1			
. TYPE OF COMPLE	TION	W.E.C.	WELLL		DRY L	OTHER_				8. Farm	or Leas	e Name
NEW THE WOL	RK [EEPEN	PLUG E	DIF	va.	OTHER			ļ		ate F	₹L 16
well X ove	<u> </u>	ELPENCI								9. Well	Vo.	
Tenneco O:	il Compa	nsz									1	,,,,,,
Address of Operator	11 Compa	11.y								10. Field and Pool, or Wildcat		
7990 IH 10	O West.	San Anto	onio. TX	7823	0					Wildcat-Devonian		
Location of Well									į			
					4			200				
IT LETTER M	LOCATED	330	FEET FA	M THE	south	LINE AN	D	330	ET FROM		7777	7]]]]]
							////			12. Cou		
west Line or	sec. 16	TWP.	11S AGE	28E	NMPM		\overline{m}	TXIIII.		Chave		Cashinghard
. Date Spudded	16. Date T	.D. Reached	1 17. Date (Compl. (Re	eady to Pi	od.) 18.			кв, кт, с	K, elc.)	19. Ele	v. Cashinghead
11/14/85	12/19	/85	N/A					69.5 GR 23. Intervals	D-4	w Tools	 ,	Cable Tools
. Total Depth	21	. Plug Back	T.D.		if Multiple Many	Compl., H	ow	Drilled F	av.			,abic 100ib
7250'									▶ 0'	- 7250		Was Directional Surve
Producing Interval	s), of this co	mpletion —	Top, Bottom,	Name								Made
											1	no
none, wel	1 P & A									12	7. Was \	Well Cored
. Type Electric and				- 1017							no	
DLL/MSFL,	/GR/CAL	(CFL/CNS/C	R/CAL		. 11		·II)				
٠.						ort all string	gs ser		TING REC	ORD	T	AMOUNT PULLED
CASING SIZE		LB./FT.	DEPTH		17	E SIZE	370	sxs Cla				0
13 3/8"	54.5	<u> </u>	350 1900		11"		550	sxs Cla	ss "C"			0
8 5/8"	24#		1900		11		1550	01.0				
			ļ				+					
			RECORD		L			30.		TUBING	RECOR)
J.				SACKS C	EMENT	SCREE	N.	SIZE	DE	PTH SE	T	PACKER SET
SIZE	TOP		OTTOM	3ACK3 C	- LINE IVI			none				
none												
Perforation Record	(I-remal si	a and numi	herl			32.	ACI	D, SHOT, FR	ACTURE,	CEMEN.	r squei	EZE, ETC.
Perioration Record	i (intervat, st	ze una nami	,,			<u> </u>		ERVAL				MATERIAL USED
												·
3.						UCTION		 		- 1		Dead on Shua in 1
rite First Production	·	Production	Method (Flow	ving, gas	lift, pump	ing - Size	and ty	pe pump)		Well	status (/	Prod. or Shut-in)
NA												as - Oil Ratio
rate of Test	Hows Tes	sted (Choke Size	Prod'n. Test P		Oil - Bbl.		Gas - MCF	Wa	ter — Bbl	. '	ds=On Autio
					<u> </u>			<u> </u>	ter – Bbl.		100.6-	avity - API (Corr.)
low Tubing Press.	Casing P		Calculated 24 How Rate	- O11 — I	361.	Gas -	- MCF	wa'	ter — BDI.		011 011	1411y = XF1 (0011)
		-		·		1			T-	st Witnes	sed Bv	~
Disposition of Gar	s (Sold, used	for fuel, ver	nted, etc.)						١٠٠	J	,	
5. List of Attachmen	ts											
					,			the base of	my knowl-	dee and	belief	
. I hereby certify the	de the inform	stien shown	on both side	s of this	jorm is tri	ie ana comp	nele k	, inc pest of t	, anowe	age and		1. 1.
/1	lan	hnds	111		_			-4			- //	1/1/86
SIGNED	on V	mas	y-	ті	TLE	rilling	z En	gineer		DATE	<u> </u>	I W UP
			71		•						/	v
			\mathcal{C}									

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeas	stern New Mexico	Noruiweste	m New Mexico
T. Anhy T. Salt B. Selt T. Yates350 T. 7 Rivers T. Queen T. Grayburg	T. Canyon T. Strawn T. Atoka 6545 T. Miss 6835 T. Devonian 7140 T. Silurian T. Montoya	T. Ojo Alamo T. Kirtland-Fruitland T. Pictured Cliffs T. Cliff House T. Menefee T. Point Lookout T. Mancos	T. Penn. "B"
T. Glorieta 2800 T. Paddock T. Blinebry T. Tubb 4230 T. Drinkard T. Abo 5020 T. Wolfcamp 5865 T. Penn	T. McKee T. Ellenburger T. Gr. Wash T. Granite T. Delaware Sand T. Bone Springs T. T.	Base Greenhorn T. Dakota T. Morrison T. Todilto T. Entrada T. Wing ate T. Chinle T. Permian T. Penn. "A"	
No. 2, from	to	. No. 5, from	toto
Include data on rate of water inflo	IMPORTA	NT WATER SANDS	
No. 3, from	to		
	FORMATION RECORD (Attac	h additional sheets if necessary)	

From	To	Thickness in Feet	Formation	From	То	Thickness in Feet	Formation
1000	1520	520	Shale w/anhy, halite				
1520	2230	710	Dolomite w/anhy				
2230	2800	570	Limestone w/Dolo	ļ		1	
2800	3100	300	Sandstone w/lime		ļ		
3100	4230	1130	Anhydrite w/SS, Dolo				
4230	4560	330	Sandstone w/anhy, Dolo		ļ	1	
4560	5020	460	Dolomite w/anhy]	1	
5020	5500	480	Shale				
5500	5865	365	Dolomite & Shale				
5865	6545	680	Limestone w/shale				
6545	6835	290	Limestone & Shale			1 1	
6835	7140	305	Limestone w/chert, shale			1 1	
7140	7250	110	Dolomite w/chert				
į.							
			•				
- 1			•				
			·				