

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	
LAND OFFICE	
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease

State ☐ Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Unit Agreement Name
2. Name of Operator Cibola Energy Corporation	8. Farm or Lease Name CX Plains
3. Address of Operator P. O. Box 1668, Albuquerque, New Mexico 87103	9. Well No. 17
4. Location of Well UNIT LETTER <u>0</u> FEET FROM THE <u>South</u> LINE AND <u>1650</u> FEET FROM THE <u>East</u> LINE, SECTION <u>19</u> TOWNSHIP <u>10S</u> RANGE <u>28E</u> N.M.P.M.	10. Field and Pool, or Wildcat Race Track San Andre
15. Elevation (Show whether DF, RT, GR, etc.) 3748.8	12. County Chaves


16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1-14-86 Spudded 12 1/4" hole with Rotary at 12:00 noon.

1-15-86 Ran 284' of 7 5/8" casing, texas pattern guide shoe and insert float. Cemented with 200 sx Class C cement with 2% CaCl. Circulated 40 sx to pit. Bump plug to 750#. Held pressure 30 minutes. WOC 18 hrs.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Karen Azar TITLE Drilling Secretary DATE 1-16-86

Original Signed By
Les A. Clements

APPROVED BY _____ TITLE _____ DATE JAN 22 1986

CONDITIONS OF APPROVAL, IF ANY:

Supervisor District 11