


STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	<input checked="" type="checkbox"/>
FILE	<input checked="" type="checkbox"/>
U.S.G.S.	<input checked="" type="checkbox"/>
LAND OFFICE	<input checked="" type="checkbox"/>
OPERATOR	<input checked="" type="checkbox"/>

OIL CONSERVATION DIVISION

SANTA FE, NEW MEXICO 87501



Form C-103
Revised 10-1-78

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
2. Name of Operator Cibola Energy Corporation		5. State Oil & Gas Lease No.
3. Address of Operator P. O. Box 1668, Albuquerque, New Mexico 87103		7. Unit Agreement Name
4. Location of Well UNIT LETTER J 1650 FEET FROM THE South LINE AND 2310 FEET FROM THE East LINE, SECTION 19 TOWNSHIP 10S RANGE 28E NMPM.		8. Farm or Lease Name CX Plains
		9. Well No. 20
		10. Field and Pool, or WHcat Race Track San Andre
15. Elevation (Show whether DF, RT, GR, etc.) 3751.2 GR		12. County Chaves

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1-8-86 Spudded 12 1/4" hole at 10:30 pm with rotary.

1-9-86 Ran 295' of 7 5/8" casing, texas pattern guide shoe and insert float. Cemented with 200 sx Class C cement with 2% CaCl2. Circulated 10 sx to pit. Bump plug to 750#. Held pressure 30 minutes. WOC 18 hrs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Karen Azar TITLE Drilling Secretary DATE 1-15-86

APPROVED BY Les A. Clements TITLE DATE JAN 22 1986

CONDITIONS OF APPROVAL, IF ANY: Supervisor District 11