

Form 100-100
(November 1983)
(Formerly 9-331)

UNITED STATES NM Oil Cons. Comm. 100
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Albany, NM 88210

Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL

NM-32351

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Royale Federal Comm.

9. WELL NO.

#1

10. FIELD AND POOL OR WILDCAT

W. Pecos Slope Abo

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 19-6S-23E

12. COUNTY OR PARISH

Chaves

13. STATE

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐
2. NAME OF OPERATOR
McKay Oil Corporation
3. ADDRESS OF OPERATOR
Post Office Box 2014, Roswell, New Mexico 88201
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface
680' FWL & 1950' FSL

RECEIVED BY

JAN 29 1987

88201 D. C. D.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4025' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Production casing

X

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

1-10-87

Ran in hole w/80 jts., 4 1/2" 9.5# casing, set @ 3359', cemented w/325 sxs. Premium Plus cement, w/2% gel, 4/10th of 1% Halliburton Lite, 3/10th of 1% CFR3, 5# salt, 1/4# flogel, 5# gilsonite, cemented 1" w/250 sxs. Howco Lite from 1400' to surface. Plug down @ 10 p.m.

18. I hereby certify that the foregoing is true and correct

SIGNED

Theresa Rodriguez

TITLE

Production Analyst

DATE 1-22-87

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD
PETER W. CHESTER
DATE

JAN 27 1987

BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA

*See Instructions on Reverse Side

