

EXISTING

PROPOS.

OBRIEN #1
660' FNL & 1900' FWL
SEC. 25-T7S-R29E
CHAVES COUNTY, NM
API # 30-005-62340
SPUD DATE: 9/23/86

60', 15 SX., SURFACE PLUG
100', 25 SX., 288-388'
100', 25 SX., PLUG 877'-977'

13 3/8" @ 333
375 SX.
CIRC.

8 5/8" @ 2328'
1150 SX.
CIRC. 100 SX.

100', 25 SX., PLUG 2278'-2378'
TAG PLUG

100', 25 SX., PLUG 3550-3450'

CUT AND PULL CASING @ +/- 5300'
100', 25 SX 1/2 IN AND 1/2 OUT OF STUB
TAG PLUG

TOC @ 5456' (CBL)

2 7/8" TUBING

S.N. @ 6460'. OPEN ENDED
PERF. 6488-6512'

CIBP @ 6425', W/ 35' CEMENT

CIBP @ 6901'
PERF. 6991-93', 7066-67', 7078-82'
5 1/2" CASING @ 7201'
425 SX.
5 1/2" X 7 5/8" = .1733 CU. FT. / FT.
425SX + 25% EXCESS=2425' FILL

PLUG @ 7410'-7510'

INSTALL DRY HOLE MARKER
CLEAN LOCATION AND RIP

PLUG @ 7890'-7990'

T.D. 8100'

T. SALT 922'

B. SALT 1232'

T. SAN ANDRES 2328'

GLORIETTA 3525'

TUBB 5013'

ABO 5780'

CISCO 7056'

MISS 7510'

DEVONIAN 7988'