INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or dampened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shell be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

			-	Ŧ	Ojo Alamo	т.	Penn. "B"
т.	Anhy	Т.	Canyon	л. Т	Kistland Kruitland	T.	Penn. "C"
т.	Salt	T.	Strawn	Г. 	Kirtland-Fruitland	т. Т	Pann (D)
B .	Selt	Т.	Atoka	Т.	Pictured Cliffs	л. т	
		T	Mice	Τ.	Cliff House	1.	Leadvine
		т	Devening	Т.	Menefee	1.	Madison
 T	-	T	Siluri an	т.	Point Lookout	1.	Elbert
		т	Montova	Τ.	Mancos	1.	MCCIacken
	329	T	Cimulant.	T.	Gallup	Т.	Ignacio Qtzte
Т.	San Andres 1232	1. T	Mokaa	Bas	se Greenhorn	Т.	Granite
τ.	Glorieta1/12	1.		т	Dakota	т.	
Т.	Patiedok <u>1850 1410</u>	т.	Ellenburger	л. т	Morrison	Т.	
T.	Blinebry	Т.	Gr. Wash	1. T	Todilto	т.	
т.	Tubb	Т.	Granite	1.		T	
т.	Drinkard	Т.	Delaware Sand	Т.	Entrada	т. Т	
Т.	Аьо 3517	Τ.	Bone Springs	. Т.	Wingate	1. m	
~	·	T		Τ.	Chinle		والمستجربين والمتكارجين ومنكان ومعتقب والتشبيب ومتاكر ومعتقات ومعتوان والمسو
		m		т	Permian		
*. T	Cisco (Bough C)	Т.		. T .	Penn "A"	Т.	······
			OIL OR GAS	S	ANDS OR ZONES		
No.	1, from			No	o. 4, from		
No.	2, from			No	5, from	•••••	to
No.	3, from		_t0	No	5. 6, from		to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1,	fromfeet.	** *** * * * * * * * * * * * * * * * * *
	frointototo	
	fromtoto	
No. 4	from	

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0 40 350 499 950 1420 1823 2090 2573 2759 2949 3330	40 350 499 950 1420 1823 2090 2573 2759 2949 3330 3459	40 310 149 451 470 403 267 483 186 190 381 129	Surface, Rock Redbeds Redbeds, Anhy Anhy Lime, Sd Anhy, Salt Lime, Anhy Anhy, Salt Lm, Anhy Anhy, Salt Anhy, Salt Anhy, Dolo Dolo, Salt	3459 3567 3668 3798	3567 3668 3798 4000	108 101 130 202	Dolo, Shale, Lime Shale Shale, Dolo Shale