

UNITED STATES DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
Artesia, NM 88210

Expires April 31, 1985
LEASE DESIGNATION AND SERIAL
NM-36193
IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED BY
OCT 14 1986
O. C. D.
ARTESIA OFFICE

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR
McKay Oil Corporation

3. ADDRESS OF OPERATOR
Post Office Box 2014, Roswell, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface
1930' FEL & 660' FSL

14. PERMIT NO. _____ 15. ELEVATIONS (Show whether DF, RT, GR, etc.)
4207' GL

7. UNIT AGREEMENT NAME _____

8. FARM OR LEASE NAME
Four Mile Draw Fed.

9. WELL NO.
#4

10. FIELD AND POOL OR WILDCAT
W. Pecos Slope Abo

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 14-6S-22E

12. COUNTY OR PARISH
Chaves

13. STATE
NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other) _____

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud & Surface csg.

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- 10-3-86 Drilled 30' 12 1/4" starter hole, rathole, mousehole.
- 10-5-86 RIH w/22 jts. of 8 5/8", 24#, J-55 API csg., set @ 901'. Cement w/150 sxs. of Class "C" cement w/3% CaCl2 and 150 sxs. of Halliburton Lite w/4% CaCl2. Plug down @ 2:45 a.m. Did not circ. cement. Ran TS indicated TOC @550'. RIH w/1" Kobe pipe. Tagged cement @ 560'. Brought cement from 560' to surface in 7 stages using 225 sxs. of Class "C" cement w/5% CaCl2, 400 gals. of Flowcheck and 7 yds. of pea gravel. Finished 1" job @ 12 noon.



18. I hereby certify that the foregoing is true and correct
SIGNED Theresa Rodriguez TITLE Production Analyst DATE 10-7-86
(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD
PETER W. CHESTER
DATE
OCT 8 1986
BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA

*See Instructions on Reverse Side