

November 1986
(Formerly 9-321)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

EXPIRATION DATE: 11-1-1988
5. LEASE DESIGNATION AND SERIAL

NM-36193

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Four Mile Draw Fed.

9. WELL NO.

#5

10. FIELD AND POOL OR WILDCAT

W. Pecos Slope Abo

11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA

Section 14-6S-22E

12. COUNTY OR PARISH 13. STATE

Chaves

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

McKay Oil Corporation

3. ADDRESS OF OPERATOR

P.O. Box 2014, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)

At surface

2080' FNL & 330' FWL

RECEIVED BY

NOV 21 1986

O. C. D.

ARTESIA, OFFICE

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4261' GL

16

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

Spud & surface csg.

X

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11-13-86 Drilled 30' of 12 1/4" starter hole, rathole, mousehole.

11-14-86 Ran in hole w/23 jts. of 8 5/8" 24#, J-55API casing., set @ 894'. Cemented w/150 sxs. of Class "C" cement w/3% CaCl₂ and 150 sxs. Haliburton Lite "C" cement w/4% CaCl₂. Plug down @ 9:30 a.m. Did not circ. cement. Ran Temp. survey, survey indicated TOC @ 650'. RIH w/1" Kobe pipe. Tagged cement @ 660'. Brought cement to surface in 6 stages using 190 sxs. Class "C" w/5% CaCl₂, 3 yds. of pea gravel, and 150 gal. of Flowcheck. Finished 1" job @ 9:30 p.m.

18. I hereby certify that the foregoing is true and correct

SIGNED Theresa Rodriguez

TITLE Production Analyst

DATE 11-18-86

(This space for Federal or State office use)

APPROVED BY

TITLE

CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD
PETER W. CHESTER
DATE

NOV 20 1986

BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA

*See Instructions on Reverse Side

OFFICE OF THE ATTORNEY GENERAL
STATE OF ARIZONA
PHOENIX, ARIZONA

