

(November 1983)  
(Formerly 9-331)

UNITED STATES DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
NM Oil Wells in Artesia, NM 88210

Expires August 31, 1985  
5 LEASE DESIGNATION AND SERIAL  
NM-36192-A  
6 IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1 OIL WELL ☐ GAS WELL ☒ OTHER ☐

2 NAME OF OPERATOR  
McKay Oil Corporation

3 ADDRESS OF OPERATOR  
P.O. Box 2014, Roswell, New Mexico 88201

4 LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface  
1780' FEL & 660' FSL

5 ELEVATIONS (Show whether D, RT, GR, etc.)  
4077' GL

6 RECEIVED BY  
NOV 13 1986  
B. C. D.  
ARTESIA, OFFICE

7 UNIT AGREEMENT NAME

8 FARM OR LEASE NAME  
Hosmer Fed.

9 WELL NO.  
#4

10 FIELD AND POOL OR WILDCAT  
W. Pecos Slope Abo

11 SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 13-6S-22E

12 COUNTY OR PARISH  
Chaves

13 STATE  
NM

16 Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF	PULL OR ALTER CASING
FRACTURE TREAT	MULTIPLE COMPLETION
SHOOT OR ACIDIZE	ABANDON*
REPAIR WELL	CHANGE PLANS
(Other)	

SUBSEQUENT REPORT OF:

WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREATMENT	ALTERING CASING
SHOOTING OR ACIDIZING	ABANDONMENT*
(Other) Spud & surface csg.	X

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17 DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11-7-86 Spudded 12 1/4" starter hole

11-8-86 Ran in hole w/22 jts. of 8 5/8", 32#, J-55 API csg. set @ 905', cemented w/150 sxs., Class "C" cement, w/3% CaCl & 150 sxs. Pace Setter Lite "C" w/4% CaCl, plug down @ 11:30 a.m. Did not circ. cement. Waited 4 hrs. to run Temperature survey, survey indicated TOC @ 600'. Ran in hole w/1" Kobe pipe, tagged @ 600', brought cmt. to surface in 8 stages using 270 sxs. Class "C" cement w/5% CaCl & 11 yds. pea gravel, 336 gals aqua fix. Finished 1" job @ 9:45 p.m.

18. I hereby certify that the foregoing is true and correct

SIGNED Theresa Rodriguez TITLE Production Analyst DATE 11-11-86

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

