

45P

UNITED STATES DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
NM Oil Cons. mission  
Artesia, NM 88210

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	2. NAME OF OPERATOR McKay Oil Corporation	3. ADDRESS OF OPERATOR Post Office Box 2014, Roswell, New Mexico 88201	4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FEL & 1980' FSL	5. PERMIT NO.	6. ELEVATIONS (Show whether DF, RT, CR, etc.) 4293' GL	7. UNIT AGREEMENT NAME	8. FARM OR LEASE NAME Lookout Federal	9. WELL NO. #1	10. FIELD AND POOL OR WILDCAT W. Pecos Slope Abo	11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA Section 10-6S-22E	12. COUNTY OR PARISH Chaves	13. STATE NM
--	--	---	--	---------------	---	------------------------	--	-------------------	---	---	--------------------------------	-----------------

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
FRACURE TREAT	MULTIPLE COMPLETION	FRACURE TREATMENT	ALTERING CASING
SPEED OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT*
REPAIR WELL	CHANGE PLANS	(Other) Spud & surface casing	

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details and give pertinent dates, including estimated date of starting any part of work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

12-22-86 Spudded 12 1/4" hole @ 3:30 p.m.

12-23-86 Ran in hole w/22 jts. 8 5/8", 32#, Limited surface casing, set @ 915', cemented w/50 sxs. Class "C" cement, w/4% CaCl, 150 sxs. Halliburton Lite, w/4% CaCl, 100 sxs. Class "C" w/2% CaCl. Plug down @ 1 a.m. Ran TS cement top @ 525', tag cement w/1" pipe. Drilling cement through 1" pipe, plug #1 @ 454', cemented w/35 sxs Class "C" cement, w/4% CaCl, plug #2 @ 485' cemented w/35 sxs. Class "C" cement, w/4% CaCl, plug #3 @ 400' cemented w/35 sxs. Class "C" cement, w/4% CaCl, plug #4 @ 299' cemented w/50 sxs. Class "C" plug #5 @ 124' cemented w/35 sxs. Class "C" plug #6 @ 250' cemented w/35 sxs. cement Class "C" cement, plug #7 @ 155' cement w/35 sxs. Class "C" cement., plug #8 @ 60', cemented w/45 sxs. Class "C".

18. I hereby certify that the foregoing is true and correct

SIGNED Theresa Rodriguez TITLE Production Analyst DATE 1-6-87  
(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_

ACCEPTED FOR RECORD  
PETER W. CHENTER  
DATE \_\_\_\_\_

JAN 14 1987

BUREAU OF LAND MANAGEMENT  
ROSWELL RESOURCE AREA

\*See Instructions on Reverse Side